Flow Rate Indicating Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-01-505-3781

| Overall Length:                                |  |
|--|--|
| 10.625 inches                                  |  |
| Media For Which Designed:                      |  |
| Air  |  |
| Inlet Connection Type:                         |  |
| Threaded                                       |  |
| End Application:                               |  |
| Panel tube assembly; asds non-soc retail stock |  |
| Integral Relief Valve:                         |  |
| Not included                                   |  |
| Meter Type:                                    |  |
| Float  |  |
| Design Type:                                   |  |
| Glass  |  |
| Unit Type:                                     |  |
| Mounted  |  |
| Scale Quantity:                                |  |
| 1  |  |
| Outlet Connection Type:                        |  |
| Threaded                                       |  |
| Scale Marking:                                 |  |
| Standard cubic feet per minute                 |  |
| Scale Type:                                    |  |
| Direct capacity reading                        |  |
| Float Quantity:                                |  |
| 1  |  |
| Tube Material:                                 |  |
| Plastic  |  |
| Mounting Method:                               |  |
| Surface panel                                  |  |
| Dial Scale Marking Range:                      |  |
| +4.0/+48.0                                     |  |
| Outlet Connection Size:                        |  |
| 0.750 inch np (male)                           |  |
| Float Type:                                    |  |
| Guided   |  |
| Float Material:                                |  |
| Steel, stainless                               |  |
| Guide Type:                                    |  |
| Solid rod                                      |  |
| Integral Heat Source:                          |  |
| Not included                                   |  |

Flow Rate Indicating Meter - Page 2 of 2



Maximum Working Pressure: 150.0 pounds per square inch

Inlet Connection Size:

0.750 inch np (male)

Metering Tube Quantity:

1

Dial Scale Reference Pointer:

Not included

Float Quantity Per Tube:

1

**Spinning Float:** 

Not included

Integral Pulsation Dampener:

Not included

Inlet Connection Position For Which Designed:

Vertical

**Outlet Connection Position For Which Designed:** 

Vertical

Alarm Signal:

Not included

Special Features:

Max operating temp: 116 degrees celsius (inavy) flowmeter

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T134-t