NSN 6680-01-533-0899

Liquid Sight Indicator - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6680-01-533-0899

1.550 inches Width Across Flats: 1.370 inches Sight Diameter: 1.050 inches Data Furnishing Method: Clear window Special Features: Type uva plexiglass window per mil-p-5425; designed for mounting in flexible barrier material or rigid wall. Maximum thickness is 0.25 inches; recommended mounting hole size 1.05 inches Material: Aluminum alloy Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625 military specification single treatment response Style Designator: Unit Of Measure: Demilitarization: No Fiig: A43400 Mil-std (military Standard): Mil-a-8625 spec.	Overall Height:
1.370 inches Sight Diameter: 1.050 inches Data Furnishing Method: Clear window Special Features: Type uva plexiglass window per mil-p-5425; designed for mounting in flexible barrier material or rigid wall. Maximum thickness is 0.25 inches; recommended mounting hole size 1.05 inches Material: Aluminum alloy Surface Treatment: Anodize Surface Treatment Specification: Mill-a-8625 millitary specification single treatment response Style Designator: Bulls eye w/cap Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig: A43400 Mil-std (military Standard):	1.550 inches
Sight Diameter: 1.050 inches Data Furnishing Method: Clear window Special Features: Type uva plexiglass window per mil-p-5425; designed for mounting in flexible barrier material or rigid wall. Maximum thickness is 0.25 inches; recommended mounting hole size 1.05 inches Material: Aluminum alloy Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625 military specification single treatment response Style Designator: Bulls eye w/cap Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A43400 Mil-std (military Standard):	Width Across Flats:
1.050 inches Data Furnishing Method: Clear window Special Features: Type uva plexiglass window per mil-p-5425; designed for mounting in flexible barrier material or rigid wall. Maximum thickness is 0.25 inches; recommended mounting hole size 1.05 inches Material: Aluminum alloy Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625 military specification single treatment response Style Designator: Bulls eye w/cap Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A43400 Mil-std (military Standard):	1.370 inches
Data Furnishing Method: Clear window Special Features: Type uva plexiglass window per mil-p-5425; designed for mounting in flexible barrier material or rigid wall. Maximum thickness is 0.25 inches; recommended mounting hole size 1.05 inches Material: Aluminum alloy Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625 military specification single treatment response Style Designator: Bulls eye w/cap Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A43400 Mil-std (military Standard):	Sight Diameter:
Clear window Special Features: Type uva plexiglass window per mil-p-5425; designed for mounting in flexible barrier material or rigid wall. Maximum thickness is 0.25 inches; recommended mounting hole size 1.05 inches Material: Aluminum alloy Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625 military specification single treatment response Style Designator: Bulls eye w/cap Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A43400 Mil-std (military Standard):	1.050 inches
Special Features: Type uva plexiglass window per mil-p-5425; designed for mounting in flexible barrier material or rigid wall. Maximum thickness is 0.25 inches; recommended mounting hole size 1.05 inches Material: Aluminum alloy Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625 military specification single treatment response Style Designator: Bulls eye w/cap Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A43400 Mil-std (military Standard):	Data Furnishing Method:
Type uva plexiglass window per mil-p-5425; designed for mounting in flexible barrier material or rigid wall. Maximum thickness is 0.25 inches; recommended mounting hole size 1.05 inches Material: Aluminum alloy Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625 military specification single treatment response Style Designator: Bulls eye w/cap Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A43400 Mil-std (military Standard):	Clear window
inches; recommended mounting hole size 1.05 inches Material: Aluminum alloy Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625 military specification single treatment response Style Designator: Bulls eye w/cap Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A43400 Mil-std (military Standard):	Special Features:
Material: Aluminum alloy Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625 military specification single treatment response Style Designator: Bulls eye w/cap Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A43400 Mil-std (military Standard):	Type uva plexiglass window per mil-p-5425; designed for mounting in flexible barrier material or rigid wall. Maximum thickness is 0.25
Aluminum alloy Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625 military specification single treatment response Style Designator: Bulls eye w/cap Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A43400 Mil-std (military Standard):	inches; recommended mounting hole size 1.05 inches
Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625 military specification single treatment response Style Designator: Bulls eye w/cap Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A43400 Mil-std (military Standard):	Material:
Anodize Surface Treatment Specification: Mil-a-8625 military specification single treatment response Style Designator: Bulls eye w/cap Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A43400 Mil-std (military Standard):	Aluminum alloy
Surface Treatment Specification: Mil-a-8625 military specification single treatment response Style Designator: Bulls eye w/cap Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A43400 Mil-std (military Standard):	Surface Treatment:
Mil-a-8625 military specification single treatment response Style Designator: Bulls eye w/cap Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A43400 Mil-std (military Standard):	Anodize
Style Designator: Bulls eye w/cap Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A43400 Mil-std (military Standard):	Surface Treatment Specification:
Bulls eye w/cap Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A43400 Mil-std (military Standard):	Mil-a-8625 military specification single treatment response
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A43400 Mil-std (military Standard):	Style Designator:
N/a Unit Of Measure: Demilitarization: No Fiig: A43400 Mil-std (military Standard):	Bulls eye w/cap
Unit Of Measure: Demilitarization: No Fiig: A43400 Mil-std (military Standard):	Shelf Life:
Demilitarization: No Fiig: A43400 Mil-std (military Standard):	N/a
No Fiig: A43400 Mil-std (military Standard):	Unit Of Measure:
No Fiig: A43400 Mil-std (military Standard):	
Fiig: A43400 Mil-std (military Standard):	Demilitarization:
A43400 Mil-std (military Standard):	No
Mil-std (military Standard):	Fiig:
	A43400
Mil-a-8625 spec.	Mil-std (military Standard):
	Mil-a-8625 spec.