

View Online at <https://aerobasegroup.com/nsn/6680-01-557-4033>

**Ac Voltage Rating:**

Between 108.0 volts and 132.0 volts

**Dc Voltage Rating:**

28.0 volts

**Frequency Rating:**

60.0 hertz

**Major Components:**

High brightness display, master transmitter assembly, linear transmitter, multimeter, test selector switch, cables (9 each)

**Inclosure Feature:**

Multiple item w/carrying case

**Test Type For Which Designed:**

Verification testing and calibration

**Operating Test Capability:**

Self test; 4hz power supply; individual transmitter; linear and total indicator

**Phase:**

Single

**Special Features:**

Tests the following transmitters and indicators built according to the following mil-specs: indicator, individual rate mil-i-25906d; indicator, individual summation mil-i-25324c/mil-i-25907c; indicator, total summation mil-i-25325a/mil-i-25908c; transmitter mil-t-8249b/mil-t-25905c, test set complies with mil-prf-28800f class 2 type equipment designed for rugged operational environments, compatible for use in vicinity of aircraft; tracked wheel vehicles; above deck applications

**Relationship To Similar Equipment:**

Physical item for pd07wrgbzoeni27

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

T228-a

**Mil-std (military Standard):**

Mil-i-25906d spec.