## NSN 6680-01-559-0749

Liquid Level Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-01-559-0749 **Overall Length:** 244.250 inches Ac Voltage Rating: 120.0 volts Frequency Rating: 60.0 hertz **Overall Diameter:** 3.380 inches **Actuation Method:** Buoyancy **End Application:** Bear water system **Electrical Connection Type:** Cable and connector plug **Internal Battery Accommodation:** Not included **Current Rating At Maximum Rated Voltage:** 15.0 amperes load **Voltage Rating At Maximum Rated Current:** 120.0 volts Float Quantity: 1 **Operating Tempurature Rating:** 140.0 degrees fahrenheit **Mounting Method:** Clamp **Maximum Current Rating:** 55.0 amperes load **Liquid Type For Which Designed:** Non-potable water and sewage **Float And Contact Positions:** Float down, contacts open Phase: Single **Special Features:** Pumping range 6.5 to 13.5 inches, has 20ft water resistant cable, high impact; corrosion resistant; pvc housing for mercury switch hermetically sealed in steel capsule, switch must be used with pumps providing integral thermal overload Shelf Life: N/a **Unit Of Measure:** 

No

Demilitarization:

## **NSN 6680-01-559-0749** Liquid Level Switch - Page 2 of 2



Fiig:

T109-d