Flow Rate Indicating Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-01-569-0364

4	
	.130 inches
	ledia For Which Designed:
	ir or water
	nlet Connection Type:
	hreaded
	ind Application:
	n/spn-4 (v) 3
	ntegral Relief Valve:
	lot included
N	leter Type:
	loat
D	Design Type:
G	Blass
U	Init Type:
N	lounted
S	cale Quantity:
1	
С	Outlet Connection Type:
Т	hreaded
S	icale Marking:
С	cu. In. Per min
S	scale Type:
C	Direct capacity reading
F	loat Quantity:
1	
Т	ube Material:
Ρ	lastic
F	loat Type:
F	ree
F	loat Material:
S	teel, corrosion resisting
Ir	ntegral Heat Source:
Ν	lot included
N	laximum Working Pressure:
1	00.0 pounds per square inch
Ir	nlet Connection Size:
1	/8 in. Npt
N	letering Tube Quantity:
1	

Not included

## NSN 6680-01-569-0364

Flow Rate Indicating Meter - Page 2 of 2



**Spinning Float:** Not included **Integral Pulsation Dampener:** Not included Inlet Connection Position For Which Designed: Horizontal Inlet Connection Device Type: Stationary **Outlet Connection Position For Which Designed:** Horizontal **Outlet Connection Device Type:** Stationary Alarm Signal: Not included **Special Features:** Tube size and float designation 4-38a Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: T134-t