## NSN 6680-01-572-8798

Liquid Quantity Indicator - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/6680-01-572-8798  |
|--|
| Scale Marking And Surface Finish:  |
| Letters nonluminous and major graduation nonluminous   |
| Scale Division Quantity:   |
| 5 single indicator single scale  |
| Current Type:  |
| Dc   |
| Dc Voltage Rating:   |
| 12.0 volts   |
| Depth:   |
| 1.938 inches   |
| End Application:   |
| Mrap buffalo mk2a2   |
| Contact Type:  |
| Plug-in socket   |
| Presentation Type:   |
| Dial   |
| Light Location:  |
| Edge   |
| Individual Marking:  |
| E-1/4-1/2-3/4-f  |
| Electrical Connection Quantity:  |
| 1  |
| Pointer Finish:  |
| Nonluminous single pointer   |
| Pointer Purpose:   |
| Liquid level   |
| Pointer Type:  |
| Indicating single pointer  |
| Illumination Color Generation Method:  |
| Red source   |
| Mounting Facility Type And Quantity:   |
| 1 clamp  |
| Case Material:   |
| Plastic  |
| Product Name:  |
| Fuel level gage  |
| Dial Outside Diameter:   |
| 2.250 inches   |
| Special Features:  |
| Bezel is polished 316 stainless steel; lens material is uv stabilized clear polycarbonate plastic; operating temperature range is -40.0 to 185.0 |
| degrees fahrenheit   |

N/a

Shelf Life:

## NSN 6680-01-572-8798

Liquid Quantity Indicator - Page 2 of 2



|  |  | eas |  |
|--|--|-----|--|

--

Demilitarization:

No

Fiig:

A533y0