## NSN 6680-01-579-9739

Flow Rate Indicating Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-01-579-9739 **Overall Length:** 7.000 inches Media For Which Designed: Liquid **Inlet Connection Type:** Threaded **Integral Relief Valve:** Not included **Accessory Components And Quantity:** 3-wire reed switch (8w 30a 120vac/100vdc) 1, ceramic magnet 1, housing 1, foam gasket 1, half-collar 2, mounting and hardware **Meter Type:** Piston/spring **Design Type:** Case **Unit Type:** Mounted **Scale Quantity:** 1 **Construction:** Inclosed w/sight window **Outlet Connection Type:** Threaded Scale Marking: Liters per minute Scale Type: Direct capacity reading **Tube Material:** Plastic **Mounting Method:** Direct line **Carrying Handle:** Not included **Dial Scale Marking Range:** +0.0/+38.0 Base: Included **Integral Heat Source:** Not included **Maximum Working Pressure:** 

**Inlet Connection Size:** 

0.750 in npt

200.0 pounds per square inch

## NSN 6680-01-579-9739

Flow Rate Indicating Meter - Page 2 of 2



Metering Tube Quantity:
1
Maximum Water Capacity In Gallons Per Minute:
5.0
Dial Scale Smallest Increment:
0.5 gpm
Dial Scale Reference Pointer:
Included
Integral Pulsation Dampener:
Not included
Inlet Connection Position For Which Designed:
Vertical or horizontal
Inlet Connection Device Type:
Stationary
Outlet Connection Position For Which Designed:
Vertical or horizontal
Outlet Connection Device Type:
Stationary
Alarm Signal:
Included
Product Name:
Inline flow meter
Special Features:
Brass fittings, viton seal material
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T134-t