## NSN 6680-01-615-2805

Flow Rate Indicating Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-01-615-2805 **Overall Length:** 10.75 inches **Inlet Connection Type:** Threaded **End Application:** Desal plnt re **Integral Relief Valve:** Not included **Accessory Components And Quantity:** Various registors and transmitters ordered separately **Indicator Type:** Float magnetically coupled to indicator in extension chamber **Design Type:** Case **Unit Type:** Mounted **Scale Quantity:** 0 **Construction:** Any acceptable **Outlet Connection Type:** Threaded **Tube Material:** Bronze **Mounting Method:** Direct line **Outlet Connection Size:** 1 inch Base: Not included **Integral Heat Source:** Not included **Maximum Working Pressure:** 150.0 pounds per square inch **Inlet Connection Size:** 1 inch **Metering Tube Quantity:** 1 **Maximum Water Capacity In Gallons Per Minute:** 70.0 **Spinning Float:** Not included

## NSN 6680-01-615-2805

Flow Rate Indicating Meter - Page 2 of 2



Integral Pulsation Dampener:
Included
Inlet Connection Position For Which Designed:
Horizontal
Inlet Connection Device Type:
Stationary
Outlet Connection Position For Which Designed:
Horizontal
Alarm Signal:
Not included
Product Name:
Indicator, sight, liquid
Special Features:
Magnetic pick up and scale sepatate accessory
Reference Data And Literature:
ltb-072-09
Supplementary Features:
Uses positive displacement wobble plate to sense flow
Type/model Designation:
Industrial rcdl
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T134-t