

View Online at <https://aerobasegroup.com/nsn/6685-00-135-0674>

**Overall Depth:**

2.750 inches

**Bolt Circle Diameter:**

5.375 inches

**Mounting Hole Diameter:**

0.219 inches

**Mounting Hole Quantity:**

3

**Overall Diameter:**

5.594 inches

**Case Material:**

Aluminum

**Case Surface Treatment:**

Enamel

**End Application:**

Poseidon material

**Graduation Unit:**

100.000 pounds

**Actuation Type:**

Double bourdon tube

**Adjustability:**

Adjustable or nonadjustable

**Scale Range:**

+0.000/+800.000 pounds pressure per square inch

**Scale Name:**

Pressure

**Dial Size:**

4-1/2 in. Dia

**Connection Quantity:**

2

**Pointer Color:**

Black and orange

**Pointer Type:**

Indicating

**Scale Marking:**

Shock resistant

**Scale Type:**

Single

**Scale Smallest Increment:**

1.000 pounds per square inch

**Connection Type:**

External

**Mounting Method:**

Surface wall

**Scale Accuracy:**

1 pct above 5 pct of range span

**Actuating Element Material:**

Nickel copper alloy

**Scale Inscription/background Color:**

Black figures on white background

**Connection Location:**

Bottom

**Protective Crystal Material:**

Plastic

**Connection Size:**

0.250 in. Npt dia

**Connector Type Vent:**

Not provided

**Specification Or Standard:**

A design and a type

**Fsc Application Data:**

Gage, pressure, dial indicating, except engine

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T179-b

**Mil-std (military Standard):**

Mil-g-18997 spec.