Indicating Temperature Control - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6685-00-350-3966

Case Material: Steel Case Surface Treatment: Zinc plated Operating Tempurature Range: +25.0/+44.0 degrees fahrenheit Maximum Voltage Rating In Volts: +25.0/+44.0 degrees fahrenheit Maximum Voltage Rating In Volts: 120.0 ac or 240.0 ac Inclosure Type: Partially enclosed Current Rating In Amps: 20.0 Terminal Location: Back Operating Range: 25. degrees f cold output to 44 degrees f warm cut in range Power Source: External Terminal Type And Quantity: 2 quick disconnect, male Phase: Single Shelf Life: N/a Unit Of Measure: Demilitarization:
Case Surface Treatment: Zinc plated Operating Tempurature Range: +25.0/+44.0 degrees fahrenheit Maximum Voltage Rating In Volts: 120.0 ac or 240.0 ac Inclosure Type: Partially enclosed Current Rating In Amps: 20.0 Terminal Location: Back Operating Range: 25 degrees f cold output to 44 degrees f warm cut in range Power Source: External Partial Type And Quantity: 2 quick disconnect, male Phase: Single Shef Life: N/a Uit Of Measure: Fromilat Type And Curre Type:
Operating Tempurature Range:+25.0/+44.0 degrees fahrenheitMaximum Voltage Rating In Volts:120.0 ac or 240.0 acInclosure Type:Partially enclosedCurrent Rating In Amps:20.0Terminal Location:BackOperating Range:25 degrees f cold output to 44 degrees f warm cut in rangePower Source:External2 quick disconnect, malePhase:SingleShelf Life:N/aUnit of Measure:Demilitarization:
Operating Tempurature Range:+25.0/+44.0 degrees fahrenheitMaximum Voltage Rating In Volts:120.0 ac or 240.0 acInclosure Type:Partially enclosedCurrent Rating In Amps:20.0Terminal Location:BackOperating Range:25 degrees f cold output to 44 degrees f warm cut in rangePower Source:External2 quick disconnect, malePhase:SingleShelf Life:N/aUnit of Measure:Image:Image:Directing Range:SingleShelf Life:N/aImage:
+25.0/+44.0 degrees fahrenheitMaximum Voltage Rating In Volts:120.0 ac or 240.0 acInclosure Type:Partially enclosedCurrent Rating In Amps:20.0Terminal Location:BackOperating Range:25 degrees f cold output to 44 degrees f warm cut in rangePower Source:External2 quick disconnect, malePhase:SingleShelf Life:NaInt of Measure:Demilitarization:
Maximum Voltage Rating In Volts:120.0 ac or 240.0 acInclosure Type:Partially enclosedCurrent Rating In Amps:20.0Terminal Location:BackOperating Range:25 degrees f cold output to 44 degrees f warm cut in rangePower Source:ExternalTerminal Type And Quantity:2 quick disconnect, malePhase:SingleShelf Life:NaDir Of Measure:Demilitarization:
120.0 ac or 240.0 ac Inclosure Type: Partially enclosed Current Rating In Amps: 20.0 Terminal Location: Back Operating Range: 25 degrees f cold output to 44 degrees f warm cut in range Power Source: External Power Source: External 2 quick disconnect, male Phase: Single Shelf Life: N/a Unit Of Measure:
Partially enclosed Current Rating In Amps: 20.0 Terminal Location: Back Operating Range: 25 degrees f cold output to 44 degrees f warm cut in range 25 degrees f cold output to 44 degrees f warm cut in range Power Source: External Power Source: External Power Source: 2 quick disconnect, male Phase: Single Shelf Life: N/a Dist of Measure:
Partially enclosed Current Rating In Amps: 20.0 Terminal Location: Back Operating Range: 25 degrees f cold output to 44 degrees f warm cut in range 25 degrees f cold output to 44 degrees f warm cut in range Power Source: External Power Source: 2 quick disconnect, male Phase: Single Shelf Life: N/a Dist Of Measure:
Current Rating In Amps:20.0Terminal Location:BackOperating Range:25 degrees f cold output to 44 degrees f warm cut in rangePower Source:ExternalTerminal Type And Quantity:2 quick disconnect, malePhase:SingleShelf Life:N/aUnit Of Measure:Demilitarization:
20.0 Ferminal Location: Back Operating Range: 25 degrees f cold output to 44 degrees f warm cut in range Power Source: External External 2 quick disconnect, male Phase: Single Shelf Life: N/a Ditt of Measure: Demilitarization:
Back
Operating Range:25 degrees f cold output to 44 degrees f warm cut in rangePower Source:ExternalExternal2 quick disconnect, malePhase:SingleShelf Life:N/aUnit Of Measure:Demilitarization:
25 degrees f cold output to 44 degrees f warm cut in range Power Source: External Terminal Type And Quantity: 2 quick disconnect, male Phase: Single Shelf Life: N/a Unit Of Measure:
25 degrees f cold output to 44 degrees f warm cut in range Power Source: External Terminal Type And Quantity: 2 quick disconnect, male Phase: Single Shelf Life: N/a Unit Of Measure:
Power Source:ExternalTerminal Type And Quantity:2 quick disconnect, malePhase:SingleShelf Life:N/aUnit Of Measure:Demilitarization:
Terminal Type And Quantity: 2 quick disconnect, male Phase: Single Shelf Life: N/a Unit Of Measure: Demilitarization:
2 quick disconnect, male Phase: Single Shelf Life: N/a Unit Of Measure: Demilitarization:
Phase: Single Shelf Life: N/a Unit Of Measure: Demilitarization:
Single Shelf Life: N/a Unit Of Measure: Demilitarization:
Shelf Life: N/a Unit Of Measure: Demilitarization:
N/a Unit Of Measure: Demilitarization:
Unit Of Measure: Demilitarization:
 Demilitarization:
Demilitarization:
No
Fiig:
A31700