

View Online at https://aerobasegroup.com/nsn/6685-00-526-8715

#### **Overall Depth:**

2.250 inches

**Bolt Circle Diameter:** 

9.625 inches

Mounting Hole Diameter:

0.281 inches

### Mounting Hole Quantity:

3

## **Overall Diameter:**

10.250 inches

## **Case Material:**

Plastic

Case Surface Treatment:

Paint, black

Graduation Unit:

10.0 inches and 100.0 pounds per square inch

# Actuation Type:

Single bourdon tube

## Adjustability:

Adjustable

# Scale Range:

+0.0 to 30.0 inches of mercury and +0.0 to 200.0 pounds pressure per square inch

# Scale Name:

Pressure and pressure-vacuum

Dial Size:

8-1/2 in. Dia

# **Connection Quantity:**

1

### Pointer Color:

White

### Pointer Type:

Indicating

### Scale Marking:

Safe range crusing combination; safe range hp turbine combination; danger zone hp turbine combination slow down to 200 rpm shut crossover valve; pressure-vacuum

Scale Type:

Multiple

### Scale Smallest Increment:

1.0 inches and 100.0 pounds per square inch

### **Connection Type:**

External

### **Mounting Method:**

Surface wall



Scale Accuracy:
1-1/2 pct entire scale; 1/4 in. Between 5 in. And 30 in.
Actuating Element Material:
Steel
Scale Inscription/background Color:
Black figures on white background
Scale Name For Which Pointer Is Designed:
Pressure-vacuum
Connection Location:
Back
Bezel Type:
Snap-on
Protective Crystal Material:
Glass
Connection Size:
0.250 in. Od tube
Connector Type Vent:
Not provided
Material:
Brass
Material:
Copper alloy
Surface Treatment:
Paint
Surface Treatment:
Paint, black
Specification Or Standard:
A design and c type
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
Т179-b