

View Online at <https://aerobasegroup.com/nsn/6685-00-527-6117>

Overall Depth:

1.290 inches

Bolt Circle Diameter:

4.250 inches

Mounting Hole Diameter:

0.157 inches

Mounting Hole Quantity:

3

Overall Diameter:

4.625 inches

Case Material:

Steel

Case Surface Treatment:

Paint, black

End Application:

Pumping assembly, flammable liquid, engine driven, 350 gpm

Graduation Unit:

40.0 pounds per square inch

Actuation Type:

Single bourdon tube

Adjustability:

Nonadjustable

Scale Range:

+0.0 to 160.0 pounds pressure per square inch

Scale Name:

Pressure

Dial Size:

3-1/2 in. Dia

Connection Quantity:

1

Pointer Color:

Black

Pointer Type:

Indicating

Scale Type:

Single

Scale Smallest Increment:

5.0 pounds per square inch

Connection Type:

External

Mounting Method:

Flush

Scale Accuracy:

2 pct middle half of range

Actuating Element Material:

Phosphor bronze

Scale Inscription/background Color:

Black figures on white background

Connection Location:

Lower

Bezel Type:

Slips-on

Protective Crystal Material:

Glass

Connection Size:

0.250 in. Npt dia

Connector Type Vent:

Not provided

Material:

Steel

Material:

Steel

Surface Treatment:

Paint

Surface Treatment:

Paint, black

Fsc Application Data:

Gage, pressure, dial indicating, except engine

Reference Number Differentiating Characteristics:

As differentiated by scale type; scale name; scale range; scale accuracy; graduation unit; scale smallest increment; scale inscription/background color; dial size; case material; case surface treatment; diameter; depth; bezel type; material; surface treatment; connection quantity; connection type; connection location; connection size; mounting method

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T179-b