Dial Indicating Pressure Gage - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6685-00-527-6156

| Graduation Unit: 50.0 pounds per square inch Actuation Type: Bourdon tube Adjustability: Adjustability: Adjustabile Scale Range: +0.0/+500.0 pounds pressure per square inch Scale Name: Pressure Dial Size: 1-1/12 in. Dia Connection Quantity: 1 Pointer Color: Yellow Pointer Type: Indicating Scale Marking: Cylinder pressure per square inch Scale Type: Indicating Scale Marking: Cylinder pressure per square inch Scale Type: Single Scale Smallest Increment: 25.0 pounds per square inch Connection Type: External Mounting Method: Surface Scale Accuracy: 2 pct entire range Actuating Element Material: Any acceptable Scale Inscription/background Color: | | |
|--|---------------|----------------------------------|
| Overall Diameter: 1.650 inches Case Material: Any acceptable Case Surface Treatment: Dull black Graduation Unit: S0.0 pounds per square inch Actuation Type: Bourdon tube Adjustability: Adjustabile Scale Range: +0.0+500.0 pounds pressure per square inch Scale Range: Pressure Dial Size: 1-1/2 in. Dia Connection Quantity: 1 Pointer Color: Yellow Pointer Type: Indicating Scale Marking: Cylinder pressure per square inch Scale Marking: Cylinder pressure per square inch Scale Marking: Cylinder pressure per square inch Scale Scale Marking: Cylinder pressure per square inch Scal | Overall Dep | oth: |
| 1.650 inches Case Material: Any acceptable Case Surface Treatment: Dull black Graduation Unit: 50.0 pounds per square inch Actuation Type: Bourdon tube Adjustability: Adjustability: Adjustabile Scale Range: +0.0/+500.0 pounds pressure per square inch Scale Name: Pressure Dial Size: 1-1/2 in. Dia Connection Quantity: 1 Pointer Color: Yellow Pointer Type: Indicating Scale Marking: Cylinder pressure per square inch Scale Scale Scale Increment: Sc1 pounds per square inch Connection Type: External Mounting Method: Surface Scale Accuracy: | 0.844 inche | S |
| Case Material: Any acceptable Case Surface Treatment: Dull black Graduation Unit: S0.0 pounds per square inch Actuation Type: Bourdon tuble Adjustability: Connection Quantity: 1 Pointer Color: Yellow S | Overall Dia | meter: |
| Any acceptable Case Surface Treatment: Dull black Graduation Unit: 50.0 pounds per square inch Actuation Type: Bourdon tube Adjustable Sociale Range: +0.0/+500.0 pounds pressure per square inch Scale Range: +0.0/+500.0 pounds pressure per square inch Scale Name: Pressure Dial Size: 1-1/2 in. Dia Connection Quantity: 1 Pointer Color: Yellow Pointer Color: Yellow Pointer Type: Indicating Scale Marking: C/jindre pressure per square inch Scale Type: Storge Scale Smallest Increment: 25.0 pounds per square inch Connection Type: External Mounting Method: Surface Scale Accuracy: 2 pot entire range Actuating Element Material: Any acceptable Scale Inscription/background Color: | 1.650 inche | S |
| Case Surface Treatment: Dull black Graduation Unit: 50.0 pounds per square inch Actuation Type: Bourdon tube Adjustability: Bolito: Patient Color: Yellow Pointer Type: Indicating Cylinder pressure per square inch Scale Marking: Cylinder pressure per square inch Scale Scale Increment: 25.0 pounds per square inch Connection Type: | Case Mater | ial: |
| Duil black Graduation Unit: 50.0 pounds per square inch Actuation Type: Bourdon tube Adjustability: Adjustabili | Any accepta | able |
| Graduation Unit: 50.0 pounds per square inch Actuation Type: Bourdon tube Adjustability: Adjustability: Adjustabile Scale Range: +0.0/+500.0 pounds pressure per square inch Scale Name: Pressure Dial Size: 1-1/12 in. Dia Connection Quantity: 1 Pointer Color: Yellow Pointer Type: Indicating Scale Marking: Cylinder pressure per square inch Scale Type: Indicating Scale Marking: Cylinder pressure per square inch Scale Type: Single Scale Smallest Increment: 25.0 pounds per square inch Connection Type: External Mounting Method: Surface Scale Accuracy: 2 pct entire range Actuating Element Material: Any acceptable Scale Inscription/background Color: | Case Surfa | ce Treatment: |
| S0.0 pounds per square inch Actuation Type: Bourdon tube Adjustability: Adjustability: Adjustability: Adjustability: Scale Range: +0.0/+500.0 pounds pressure per square inch Scale Name: Pressure Dial Size: 1-1/2 in. Dia Connection Quantity: 1 Pointer Color: Yellow Pointer Type: Indicating Scale Marking: Cylinder pressure per square inch Scale Type: Scale Scale Increment: 25.0 pounds per square inch Scale Scale Increment: 25.0 pounds per square inch Scale Acutary: 2 pounds per square inch Scale Comection Type: External Mounting Method: Surface Scale Acutary: 2 pot entire range Actuating Element Material: Any acceptable Scale Inscription/background Color: | Dull black | |
| Actuation Type: Bourdon tube Adjustability: Adjustability: Adjustability: Adjustability: Adjustability: Scale Range: +0.0/+500.0 pounds pressure per square inch Scale Name: Pressure Dial Size: 1-1/2 in. Dia Connection Quantity: 1 Pointer Color: Yellow Pointer Type: Indicating Scale Marking: Cylinder pressure per square inch Scale Type: Scale Scale Increment: 25.0 pounds per square inch Scale Scale Increment: 25.0 pounds per square inch Scale Acuarage: External Mounting Method: Surface Scale Accuracy: 2 pot entire range Actuating Element Material: Any acceptable Scale Inscription/background Color: | Graduation | Unit: |
| Bourdon tube Adjustability: Adjustability: Adjustability: Adjustability: Adjustability: Sale Range: 40.0/+500.0 pounds pressure per square inch Scale Name: Pressure Pressure Dial Size: 1-1/2 in. Dia Connection Quantity: 1 Pointer Color: Yellow Pointer Type: Indicating Scale Marking: Cylinder pressure per square inch Scale Smallest Increment: 25.0 pounds per square inch Connection Type: External Mounting Method: Surface Scale Accuracy: 2 pct entire range Actuating Element Material: Any acceptable Scale Inscription/background Color: Comet Color: C | 50.0 pounds | s per square inch |
| Adjustability: Adjustable Scale Range: +0.0/+500.0 pounds pressure per square inch Scale Name: Pressure Pressure Dial Size: 1-1/2 in. Dia Connection Quantity: 1-1/2 in. Dia Scale Marking: Cylinder pressure per square inch Scale Marking: Cylinder pressure per square inch Scale Smallest Increment: 25.0 pounds per square inch Scale Smallest Increment: 25.0 pounds per square inch Connection Type: External Mounting Method: Surface Scale Accuracy: 2 pct entire range Actuating Element Material: Any acceptable Scale Inscription/background Color: | Actuation 1 | Гуре: |
| Adjustable Scale Range: +0.0/+500.0 pounds pressure per square inch Scale Name: Pressure Pressure Iressure Dial Size: 1-1/2 in. Dia Connection Quantity: 1 Pointer Color: Yellow Pointer Type: Indicating Scale Marking: Cylinder pressure per square inch Scale Type: Single Scale Smallest Increment: 25.0 pounds per square inch Connection Type: External Mounting Method: Surface Scale Accuracy: 2 pct entire range Actuating Element Material: Any acceptable Scale Inscription/background Color: | Bourdon tub | De |
| Scale Range: +0.0/+500.0 pounds pressure per square inch Scale Name: Pressure Dial Size: 1-1/2 in. Dia Connection Quantity: 1 Pointer Color: Yellow Pointer Type: Indicating Scale Marking: Cylinder pressure per square inch Scale Type: Single Scale Smallest Increment: 25.0 pounds per square inch Connection Type: External Mounting Method: Surface Scale Accuracy: 2 pet entire range Actuating Element Material: Any acceptable Scale Inscription/background Color: | Adjustabilit | ty: |
| +0.0/+500.^o pounds pressure per square inch Scale Name: Pressure Dial Size: 1-1/2 in. Dia Connection Quantity: 1 Pointer Color: Yellow Pointer Type: Indicating Scale Marking: Cylinder pressure per square inch Scale Type: Single Scale Smallest Increment: 25.0 pounds per square inch Connection Type: External Mounting Method: Surface Scale Accuracy: 2 pct entire range Actuating Element Material: Any acceptable Scale Inscription/background Color: | Adjustable | |
| Scale Name: Pressure Dial Size: 1 1-1/2 in. Dia Connection Quantity: 1 Pointer Color: Yellow Pointer Type: Indicating Scale Marking: Cylinder pressure per square inch Scale Type: Single Scale Smallest Increment: 25.0 pounds per square inch Connection Type: External Mounting Method: Surface Scale Accuracy: 2 pot entire range Actuating Element Material: Any acceptable Scale Inscription/background Color: | Scale Rang | je: |
| Pressure Dial Size: 1-1/2 in. Dia Connection Quantity: 1 Pointer Color: Yellow Pointer Type: Indicating Scale Marking: Cylinder pressure per square inch Scale Marking: Cylinder pressure per square inch Scale Type: Single Scale Smallest Increment: 25.0 pounds per square inch Connection Type: External Mounting Method: Surface Scale Accuracy: 2 pct entire range Actuating Element Material: Any acceptable | +0.0/+500.0 | pounds pressure per square inch |
| Dial Size: 1-1/2 in. Dia Connection Quantity: 1 Pointer Color: Yellow Pointer Type: Indicating Scale Marking: Cylinder pressure per square inch Scale Type: Stale Smallest Increment: 25.0 pounds per square inch Connection Type: External Mounting Method: Surface Scale Accuracy: 2 pct entire range Actuating Element Material: Any acceptable Scale Inscription/background Color: | Scale Name | e: |
| 1-1/2 in. Dia Connection Quantity: 1 Pointer Color: Yellow Pointer Type: Indicating Scale Marking: Cylinder pressure per square inch Scale Type: Single Scale Smallest Increment: 25.0 pounds per square inch Connection Type: External Mounting Method: Surface Scale Accuracy: 2 pct entire range Actuating Element Material: Any acceptable Scale Inscription/background Color: | Pressure | |
| Connection Quantity: 1 Pointer Color: Yellow Pointer Type: Indicating Scale Marking: Cylinder pressure per square inch Scale Type: Single Scale Smallest Increment: 25.0 pounds per square inch Connection Type: External Mounting Method: Surface Scale Accuracy: 2 pct entire range Actuating Element Material: Any acceptable Scale Inscription/background Color: | Dial Size: | |
| 1 Pointer Color: Yellow Pointer Type: Indicating Scale Marking: Cylinder pressure per square inch Scale Type: Single Scale Smallest Increment: 25.0 pounds per square inch Connection Type: External Mounting Method: Surface Scale Accuracy: 2 pct entire range Actuating Element Material: Any acceptable Scale Inscription/background Color: | 1-1/2 in. Dia | a |
| Pointer Color: Yellow Pointer Type: Indicating Scale Marking: Cylinder pressure per square inch Scale Type: Single Scale Smallest Increment: 25.0 pounds per square inch Connection Type: External Mounting Method: Surface Scale Accuracy: 2 pct entire range Actuating Element Material: Any acceptable Scale Inscription/background Color: | Connectior | n Quantity: |
| Yellow Pointer Type: Indicating Scale Marking: Cylinder pressure per square inch Scale Type: Single Scale Smallest Increment: 25.0 pounds per square inch Connection Type: External Mounting Method: Surface Scale Accuracy: 2 pct entire range Actuating Element Material: Any acceptable Scale Inscription/background Color: | 1 | |
| Pointer Type: Indicating Scale Marking: Cylinder pressure per square inch Scale Type: Single Scale Smallest Increment: 25.0 pounds per square inch Connection Type: External Mounting Method: Surface Scale Accuracy: 2 pct entire range Actuating Element Material: Any acceptable | Pointer Col | lor: |
| Indicating Scale Marking: Cylinder pressure per square inch Scale Type: Single Scale Smallest Increment: 25.0 pounds per square inch Connection Type: External Mounting Method: Surface Scale Accuracy: 2 pct entire range Actuating Element Material: Any acceptable | Yellow | |
| Scale Marking: Cylinder pressure per square inch Scale Type: Single Scale Smallest Increment: 25.0 pounds per square inch Connection Type: External Mounting Method: Surface Scale Accuracy: 2 pct entire range Actuating Element Material: Any acceptable Scale Inscription/background Color: | Pointer Typ | be: |
| Cylinder pressure per square inch Scale Type: Single Scale Smallest Increment: 25.0 pounds per square inch Connection Type: External Mounting Method: Surface Scale Accuracy: 2 pct entire range Actuating Element Material: Any acceptable Scale Inscription/background Color: | Indicating | |
| Scale Type: Single Scale Smallest Increment: 25.0 pounds per square inch Connection Type: External Mounting Method: Surface Scale Accuracy: 2 pct entire range Actuating Element Material: Any acceptable Scale Inscription/background Color: | Scale Mark | ing: |
| Single Scale Smallest Increment: 25.0 pounds per square inch Connection Type: External Mounting Method: Surface Scale Accuracy: 2 pct entire range Actuating Element Material: Any acceptable Scale Inscription/background Color: | Cylinder pre | essure per square inch |
| Scale Smallest Increment: 25.0 pounds per square inch Connection Type: External Mounting Method: Surface Scale Accuracy: 2 pct entire range Actuating Element Material: Any acceptable Scale Inscription/background Color: | Scale Type | : |
| 25.0 pounds per square inch Connection Type: External Mounting Method: Surface Scale Accuracy: 2 pct entire range Actuating Element Material: Any acceptable Scale Inscription/background Color: | Single | |
| Connection Type: External Mounting Method: Surface Scale Accuracy: 2 pct entire range Actuating Element Material: Any acceptable Scale Inscription/background Color: | Scale Smal | lest Increment: |
| External Mounting Method: Surface Scale Accuracy: 2 pct entire range Actuating Element Material: Any acceptable Scale Inscription/background Color: | 25.0 pounds | s per square inch |
| Mounting Method: Surface Scale Accuracy: 2 pct entire range Actuating Element Material: Any acceptable Scale Inscription/background Color: | Connectior | туре: |
| Surface Scale Accuracy: 2 pct entire range Actuating Element Material: Any acceptable Scale Inscription/background Color: | External | |
| Scale Accuracy: 2 pct entire range Actuating Element Material: Any acceptable Scale Inscription/background Color: | Mounting M | lethod: |
| 2 pct entire range Actuating Element Material: Any acceptable Scale Inscription/background Color: | Surface | |
| Actuating Element Material: Any acceptable Scale Inscription/background Color: | Scale Accu | iracy: |
| Any acceptable Scale Inscription/background Color: | 2 pct entire | range |
| Scale Inscription/background Color: | Actuating E | Element Material: |
| | Any accepta | able |
| | | |
| Tellow luminous ligures on black background | | nous figures on black background |

Dial Indicating Pressure Gage - Page 2 of 2



Connection Location:

Back

Protective Crystal Material:

Plastic

Connection Size:

0.125 in. Npt dia

Connector Type Vent:

Not provided

Product Name:

Gage, pressure, except engine, low-pressure oxygen type 1

Fsc Application Data:

Gage, pressure dial indicating, except engine

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T179-b