Dial Indicating Pressure Gage - Page 1 of 2



•••	ew Online at https://aerobasegroup.com/nsn/6685-00-587-0866
Bo	olt Circle Diameter:
5.	375 inches
M	ounting Hole Diameter:
0.2	219 inches
M	ounting Hole Quantity:
3	
Ca	ase Material:
AI	uminum alloy
Ca	ase Surface Treatment:
Er	namel, baked
A	ccessory Components And Quantity:
Ni	pple 1
A	ctuation Type:
Bo	purdon tube
A	djustability:
Ac	djustable
Sc	cale Range:
+(	0.0/+3000.0 pounds pressure per square inch
Sc	cale Name:
Po	punds pressure
Di	al Size:
4-	1/2 in. Dia
C	onnection Quantity:
1	
Po	binter Color:
BI	ack and red
Po	pinter Type:
١n	dicating and reference
Sc	cale Marking:
Ps	sig
Sc	cale Type:
Si	ngle
Sc	cale Smallest Increment:
20	0.0 pounds per square inch
C	onnection Type:
E>	kternal
M	ounting Method:
Fŀ	ush
Sc	cale Accuracy:
	pct entire range
	ctuating Element Material:
	ckel copper alloy



Scale Inscription/background Color:

Black figures, white background

**Connection Location:** 

Тор

Protective Crystal Material:

Plastic

# **Connection Size:**

0.250 in. Welding nipple

#### **Connector Type Vent:**

Not provided

## **Criticality Code Justification:**

Zzzy

# Special Features:

Nipple will be nickel copper alloy

#### **Reference Number Differentiating Characteristics:**

Material will be in accordance with ships partscontrol center activity hx quality control, manufacturing and testing specifications

#### Shelf Life:

N/a

---

### Unit Of Measure:

Demilitarization:

# Yes - demil/mli

Fiig:

# T179-b

.....