Steel, stainless

Dial Indicating Pressure Gage - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6685-00-726-4839

| Ov | rerall Depth: |
|------|--|
| 2.5 | i63 inches |
| Во | It Circle Diameter: |
| 7.0 | 100 inches |
| Ov | rerall Diameter: |
| 7.5 | 563 inches |
| Ca | se Material: |
| Alu | ıminum |
| Ca | se Surface Treatment: |
| Bla | ack finish |
| Gra | aduation Unit: |
| 5.0 | 000 pounds per square inch |
| Ac | tuation Type: |
| Sir | ngle bourdon tube |
| Ad | ljustability: |
| Ad | justable |
| Sc | ale Range: |
| +0. | .000 to 60.000 pounds pressure per square inch |
| Sc | ale Name: |
| Pre | essure |
| Dia | al Size: |
| 6 ir | n. Dia |
| Co | nnection Quantity: |
| 1 | |
| Ро | inter Color: |
| Bla | ack |
| Ро | inter Type: |
| Ind | licating |
| Sc | ale Type: |
| Sir | ngle |
| Sc | ale Smallest Increment: |
| 0.2 | 200 pounds per square inch |
| Co | nnection Type: |
| Ext | ternal |
| Мо | ounting Method: |
| Se | miflush panel and stud |
| Stu | ud Quantity: |
| 3 | |
| Sc | ale Accuracy: |
| 1/2 | 2 of 1 pct accuracy rating entire range |
| Ac | tuating Element Material: |
| 0.1 | |



Scale Inscription/background Color:

Black figures on white background

Connection Location:

Lower back

Bezel Type:

Hinge

Protective Crystal Material:

Glass

Connection Size:

0.500 in. Npt

Stud Location:

In panel flange

Connector Type Vent:

Not provided

Special Features:

Mirrored test gage dial, test gage pointer w/overload stop, solid wall safety plate between dial and movement, spring mounted blow out plate

at back of case

Material:

Steel

Material:

Steel

Surface Treatment:

Black finish

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

T179-b