Beryllium copper



View Online at https://aerobasegroup.com/nsn/6685-00-752-8658

VIEW	
Ove	rall Depth:
4.28	1 inches
Bolt	Circle Diameter:
7.00	0 inches
Ove	rall Diameter:
7.50	0 inches
Case	e Material:
Alum	ninum
Case	e Surface Treatment:
Resi	n, epoxy
Grad	Juation Unit:
10.0	pounds
Actu	ation Type:
Doul	ble bellows
Adju	istability:
Adju	stable
Scal	e Range:
+0.0	to 150.0 pounds pressure per square inch
Scal	e Name:
Pres	sure
Dial	Size:
6 in.	Dia
Con	nection Quantity:
4	
Poin	ter Color:
Whit	e
Poin	ter Type:
Indic	ating
Scal	е Туре:
Sing	le
Scal	e Smallest Increment:
1.00	0 pounds
Con	nection Type:
Inter	nal
Mou	nting Method:
Flus	n panel
Stud	Quantity:
4	
Scal	e Accuracy:
1/2 p	oct entire range
Actu	ating Element Material:
D	



Scale Inscription/background Color:

White figures on black background

Connection Location:

Upper and lower

Bezel Type:

Slips-on

Protective Crystal Material:

Glass

Connection Size:

1/4 in. Npt

Stud Location:

Back

Connector Type Vent:

Not provided

Material:

Aluminum

Material:

Aluminum

Surface Treatment:

Resin, epoxy

Reference Number Differentiating Characteristics:

Single reading scale, dial data, pointer data and connection data

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T179-b