

View Online at <https://aerobasegroup.com/nsn/6685-00-860-0977>

Overall Depth:

2.500 inches

Bolt Circle Diameter:

4.250 inches

Mounting Hole Diameter:

0.218 inches

Mounting Hole Quantity:

3

Overall Diameter:

4.750 inches

Case Material:

Aluminum

Case Surface Treatment:

Enamel, gray

End Application:

Systems, d2n2; chilled water a/c systems; poseidon material

Graduation Unit:

20.0 degrees and 10.0 inches and 20.0 pounds per square inch

Actuation Type:

Single bourdon tube

Adjustability:

Nonadjustable

Scale Range:

-50.0/+116.0 degrees fahrenheit and +0.0/+30.0 inches of mercury and +0.0/+150.0 pounds pressure per square inch

Scale Name:

Pressure and vacuum and temperature

Dial Size:

3-1/2 in. Dia

Connection Quantity:

1

Pointer Color:

Black and red

Pointer Type:

Indicating and reference

Scale Marking:

Dial marked refrigerant 12, in. Hg, vac, psig

Scale Type:

Multiple

Scale Smallest Increment:

20.0 degrees and 2.0 inches and 2.0 pounds per square inch

Connection Type:

External

Mounting Method:

Flush

Scale Accuracy:

Above 5 pct of range span; above 5 pct of range span; above 5 pct of range span

Actuating Element Material:

Nickel copper alloy

Scale Inscription/background Color:

Black marking on white background; black marking on white background; red marking on white background

Scale Name For Which Pointer Is Designed:

Pressure and vacuum and temperature

Connection Location:

Back

Protective Crystal Material:

Plastic

Connection Size:

0.250 in. Tube

Connector Type Vent:

Not provided

Specification Or Standard:

A design and a type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T179-b

Mil-std (military Standard):

Mil-g-18997 spec.