

View Online at <https://aerobasegroup.com/nsn/6685-00-974-6532>

Overall Depth:

2.719 inches

Bolt Circle Diameter:

5.375 inches

Mounting Hole Diameter:

0.219 inches

Mounting Hole Quantity:

3

Overall Diameter:

4.969 inches

Case Material:

Aluminum, die cast

Case Surface Treatment:

Enamel, gray

End Application:

Poseidon material; combat sys support equipment

Graduation Unit:

10.0 inches of mercury and 5.0 pounds per square inch

Actuation Type:

Single bourdon tube

Adjustability:

Adjustable or nonadjustable

Scale Range:

+0.0/+30.0 inches of mercury and +0.0/+30.0 pounds pressure per square inch

Scale Name:

Pressure-vacuum

Dial Size:

4-1/2 in. Dia

Connection Quantity:

1

Pointer Color:

Black and red

Pointer Type:

Indicating and reference

Scale Marking:

Shock resistant

Scale Type:

Single

Scale Smallest Increment:

1.0 inches of mercury and 1.0 pounds per square inch

Connection Type:

External

Mounting Method:

Flush panel

Scale Accuracy:

Porm 1 pct full range

Actuating Element Material:

Nickel copper aluminum alloy

Scale Inscription/background Color:

Black figures on white background

Scale Name For Which Pointer Is Designed:

Pressure-vacuum

Connection Location:

Bottom

Protective Crystal Material:

Plastic

Connection Size:

0.250 in. Tube

Connector Type Vent:

Not provided

Specification Or Standard:

A design and c type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T179-b

Mil-std (military Standard):

Mil-g-18997 spec.