Dial Indicating Pressure Gage - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6685-01-010-2663

030 inches plt Circle Diameter: 375 inches punting Hole Diameter: 219 inches punting Hole Quantity: verall Diameter: 090 inches ase Material: uminum, cast ase Surface Treatment:
375 inches punting Hole Diameter: 219 inches punting Hole Quantity: verall Diameter: 090 inches ase Material: uminum, cast
ounting Hole Diameter: 219 inches ounting Hole Quantity: verall Diameter: 090 inches ase Material: uminum, cast
219 inches ounting Hole Quantity: verall Diameter: D90 inches ase Material: uminum, cast
ounting Hole Quantity: verall Diameter: 090 inches ase Material: uminum, cast
verall Diameter: 090 inches ase Material: uminum, cast
090 inches ase Material: uminum, cast
090 inches ase Material: uminum, cast
ase Material: uminum, cast
uminum, cast
ase Surface Treatment:
namel, black
nd Application:
rcraft, thunderbolt ii, a-10
raduation Unit:
D pounds per square inch
ctuation Type:
aphragm
ljustability:
ljustable
cale Range:
0.0/+5000.0 pounds pressure per square inch
cale Name:
essure
al Size:
1/2 in. Dia
onnection Quantity:
sinter Color:
ack
binter Type:
dicating
cale Type:
ngle
cale Smallest Increment:
D pounds per square inch
onnection Type:
ternal

Flush flange



Scale Accuracy:
1/2 of 1 pct entire range
Actuating Element Material:
Nickel ironalloy
Scale Inscription/background Color:
Black markings on white background
Connection Location:
Lower
Bezel Type:
Hinge
Protective Crystal Material:
Glass
Connection Size:
0.250 in. Npt
Connector Type Vent:
Not provided
Material:
Steel
Material:
Steel
Surface Treatment:
Enamel
Surface Treatment:
Enamel, black
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
Т179-b