

View Online at <https://aerobasegroup.com/nsn/6685-01-179-1826>

Case Material:

Aluminum alloy

Point Quantity:

8 and 4

Accessory Components And Quantity:

Rechareable ni-cad battery pack

Scale Calibration:

Nbs certification

Installation Design:

Portable

Scale Range:

-418.0/+2500.0 degrees

Scale Type:

Meter dial

Scale Smallest Increment:

0.1 degrees

Mounting Method:

Portable metal case

Measurement Type:

Millivolt circuit

Scale Accuracy:

0.1 percent

Indicating Point Type:

Multiple

Err Default:

Err default

Err Default:

Err default

Case Type:

Carrying case w/handle

Special Features:

Consists of an 8 channel selector which measures or outputs the proper current to test and calibrate j, k, t, e, r, s, and c thermocouples and meters as well as millivolt circuits; an offposition, t/c measure, output, and self-test sw, coarse and fine adjust knob; a and b channel thermocouple sockets for comparison readings to a master; self tests for low battery, temperature, overrange, neg. Temperature, open thermocouple, input, and input error; input voltage 110 vac 47 to 400 hz

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T179-b