

View Online at <https://aerobasegroup.com/nsn/6685-01-224-4282>

Overall Depth:

26.250 inches

Overall Height:

45.000 inches

Overall Width:

45.250 inches

Ac Voltage Rating:

Between 208.0 volts and 230.0 volts

Frequency Rating:

60.0 hertz

Mounting Configuration:

Free standing cabinet on castors

Unpackaged Unit Weight:

450.000 pounds

Calibration Type:

Deg celsius and degrees fahrenheit

Instrument Calibration Range:

Cold bath -100 to +70 degrees c (-148 to +158 degrees f); hot bath +60 to +300 degrees c (+140 to +572 degrees f)

Calibration Accuracy Rating:

100 to -40 degrees c - porm 5 degrees c; -40 to +150 degrees c - porm 1 degrees c; +150 to +300 degrees c - porm 5 degrees c

Phase:

Single

Special Features:

C/o two test wells, each well is 2.6"dia x 11/3" deep (60 cubic inches) and have a 0.25" deep mercury trap. Transfer fluids: cold bath - halocarbon 0.8; hot bath - dow 710.

Functional Description:

Consists of 2 independently operable bath systems. Each bath has its own tank with a constant level test well & pump. Each has its own temperature controller, probe, & heating and colling systems. Seperate front panel power controls, labeled hot bath and cold bath, allow independent power up and use.

Reference Data And Literature:

Commercial manual

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T263-b