## NSN 6685-01-244-0262

Dial Indicating Differential Gage - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6685-01-244-0262

Mounting Hole Diameter:
0.281 inches
Mounting Hole Quantity:
4
Case Material:
Aluminum
Graduation Unit:
2.0 pounds per square inch
Actuation Type:
Piston
Adjustability:
Nonadjustable
Scale Range:
+0.0/+30.0 pounds pressure per square inch or +0.0/+2.1 kilograms per square centimeter
Scale Name:
Differential pressure
Connection Quantity:
2
Pointer Type:
Indicating
Scale Type:
Multiple and vertical
Scale Smallest Increment:
1.0 pounds per square inch
Connection Type:
Internal
Mounting Method:
Screw
Scale Accuracy:
0.5 differential at pressures up to 300 psi
Connection Location:
Bottom and top left side
Connection Size:
1/4 inch npt
Special Features:
1designed for use with fuels; 4th scale is 0 to 200 kpa; front face of scale plate has psi and kpa; back face has bar and kgcm squared;
built in filter protection; maximum operating pressure 300 psi; temp range -30 to +160 degrees f (-34 to 71 degrees c)
Reference Data And Literature:
Commercial catalog

6685-01-324-4702 has stainless steel body; 6685-01-288-9830 has special seals that allow operation down to -50 degrees c (-58 degrees f)

Shelf Life: N/a

**Relationship To Similar Equipment:** 

## NSN 6685-01-244-0262

Dial Indicating Differential Gage - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

T179-b