

View Online at <https://aerobasegroup.com/nsn/6685-01-301-6201>

**Current Type:**

Ac

**Ac Voltage Rating:**

115.0 volts

**End Application:**

Jet engine fuel control test stand

**Presentation Type:**

Digital display

**Scale Range:**

+0.1/+200.0 display digit range single indicator single scale

**Electrical Connection Quantity:**

1

**Mounting Facility Type And Quantity:**

1 bracket

**Display Type:**

Light emitting diode

**Display Digit Quantity:**

5

**Phase:**

Single

**Special Features:**

Digital pressure indicator; media air; pressure range 0 to 200 psia; calibration span 0 to 150 psia; operating temp limit 50 degrees f to 120 degrees f; storage temp -20 degrees f to 130 degrees f; speed of response 250 milliseconds for full scale traverse; display has factory located decimal point; pressure repeatability type 0.005 percent full scale; accuracy 0.05 percent of calibrated range total error; zero adjust; span adjust internal; overpressure capability type 200 percent of rated span; warmup time 2 hours total warmup time for full stability; bcd output 8421 binary coded decimal; mating 25 pin d type cable connector; pressure connection 1/4 inch npt female; mounting, unit design allows for retrofit directly into existing panel mounted support brackets as a direct replacement for ashcroft digigauge model 7580

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A533y0