NSN 6685-01-324-6326

Humidity-temperature Transmitter Group - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6685-01-324-6326

| End Application: Markivb Unpackaged Unit Length: 6.375 inches Unpackaged Unit Width: 3.125 inches Unpackaged Unit Height: 2.250 inches Special Features: Electrical connections, ac supply voltage: 5 wires plus ground; power: 115 vac; output 2x4-20ma; probe dimensions: 100mmx1 matl: delrin; accuracy: porm 2 pct th from 0 to 100 pct rh at 77 deg. F; measuring range 0 to 100 pct rh; wiring type: terminals 1 2cable grips standard Functional Description: Measures relative humidity with acapacitive sensor & temp. With precision platinum rtd Unpackaged Unit Weight: 1.800 pounds | · · |
|--|-----------|
| Unpackaged Unit Length: 6.375 inches Unpackaged Unit Width: 3.125 inches Unpackaged Unit Height: 2.250 inches Special Features: Electrical connections, ac supply voltage: 5 wires plus ground; power: 115 vac; output 2x4-20ma; probe dimensions: 100mmx1 matl: delrin; accuracy: porm 2 pct th from 0 to 100 pct rh at 77 deg. F; measuring range 0 to 100 pct rh; wiring type: terminals 1 2cable grips standard Functional Description: Measures relative humidity with acapacitive sensor & temp. With precision platinum rtd Unpackaged Unit Weight: | - |
| 6.375 inches Unpackaged Unit Width: 3.125 inches Unpackaged Unit Height: 2.250 inches Special Features: Electrical connections, ac supply voltage: 5 wires plus ground; power: 115 vac; output 2x4-20ma; probe dimensions: 100mmx1 matl: delrin; accuracy: porm 2 pct th from 0 to 100 pct rh at 77 deg. F; measuring range 0 to 100 pct rh; wiring type: terminals 1 2cable grips standard Functional Description: Measures relative humidity with acapacitive sensor & temp. With precision platinum rtd Unpackaged Unit Weight: | • |
| Unpackaged Unit Width: 3.125 inches Unpackaged Unit Height: 2.250 inches Special Features: Electrical connections, ac supply voltage: 5 wires plus ground; power: 115 vac; output 2x4-20ma; probe dimensions: 100mmx1 matl: delrin; accuracy: porm 2 pct th from 0 to 100 pct rh at 77 deg. F; measuring range 0 to 100 pct rh; wiring type: terminals 1 2cable grips standard Functional Description: Measures relative humidity with acapacitive sensor & temp. With precision platinum rtd Unpackaged Unit Weight: | • |
| 3.125 inches Unpackaged Unit Height: 2.250 inches Special Features: Electrical connections, ac supply voltage: 5 wires plus ground; power: 115 vac; output 2x4-20ma; probe dimensions: 100mmx1 matl: delrin; accuracy: porm 2 pct th from 0 to 100 pct rh at 77 deg. F; measuring range 0 to 100 pct rh; wiring type: terminals 1 2cable grips standard Functional Description: Measures relative humidity with acapacitive sensor & temp. With precision platinum rtd Unpackaged Unit Weight: | - |
| Unpackaged Unit Height: 2.250 inches Special Features: Electrical connections, ac supply voltage: 5 wires plus ground; power: 115 vac; output 2x4-20ma; probe dimensions: 100mmx1 matl: delrin; accuracy: porm 2 pct th from 0 to 100 pct rh at 77 deg. F; measuring range 0 to 100 pct rh; wiring type: terminals 1 2cable grips standard Functional Description: Measures relative humidity with acapacitive sensor & temp. With precision platinum rtd Unpackaged Unit Weight: | • |
| 2.250 inches Special Features: Electrical connections, ac supply voltage: 5 wires plus ground; power: 115 vac; output 2x4-20ma; probe dimensions: 100mmx1 matl: delrin; accuracy: porm 2 pct th from 0 to 100 pct rh at 77 deg. F; measuring range 0 to 100 pct rh; wiring type: terminals 1 2cable grips standard Functional Description: Measures relative humidity with acapacitive sensor & temp. With precision platinum rtd Unpackaged Unit Weight: | - |
| Special Features: Electrical connections, ac supply voltage: 5 wires plus ground; power: 115 vac; output 2x4-20ma; probe dimensions: 100mmx1 matl: delrin; accuracy: porm 2 pct th from 0 to 100 pct rh at 77 deg. F; measuring range 0 to 100 pct rh; wiring type: terminals 1 2cable grips standard Functional Description: Measures relative humidity with acapacitive sensor & temp. With precision platinum rtd Unpackaged Unit Weight: | - |
| Electrical connections, ac supply voltage: 5 wires plus ground; power: 115 vac; output 2x4-20ma; probe dimensions: 100mmx1 matl: delrin; accuracy: porm 2 pct th from 0 to 100 pct rh at 77 deg. F; measuring range 0 to 100 pct rh; wiring type: terminals 1 2cable grips standard Functional Description: Measures relative humidity with acapacitive sensor & temp. With precision platinum rtd Unpackaged Unit Weight: | • |
| matl: delrin; accuracy: porm 2 pct th from 0 to 100 pct rh at 77 deg. F; measuring range 0 to 100 pct rh; wiring type: terminals 1 2cable grips standard Functional Description: Measures relative humidity with acapacitive sensor & temp. With precision platinum rtd Unpackaged Unit Weight: | • |
| 2cable grips standard Functional Description: Measures relative humidity with acapacitive sensor & temp. With precision platinum rtd Unpackaged Unit Weight: | 2 awg max |
| Functional Description: Measures relative humidity with acapacitive sensor & temp. With precision platinum rtd Unpackaged Unit Weight: | |
| Measures relative humidity with acapacitive sensor & temp. With precision platinum rtd Unpackaged Unit Weight: | |
| Unpackaged Unit Weight: | |
| | |
| 1.800 pounds | |
| | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A23800 | |