

View Online at <https://aerobasegroup.com/nsn/6685-01-382-4699>

**Operating Temperature Range:**

-20.0/+60.0 degrees celsius

**Measurement Type:**

Digital

**Measurement Range:**

+10.0/+100.0 percent relative humidity

**Scale Accuracy Rating:**

Humidity accuracy +/- 2 percent rh, temp accuracy +/- 0.4 degrees f

**Special Features:**

System consists of a humidity/temp indicator w/digital display and humidity/temp probe; probe connected to display by wire; dew point temp 0 degrees c to 40 degrees c below ambient temp; outputs: dewpoint temp 0 to 1 volt for -40 to 60 degrees c, ambient temp 0 to 1 volt for -40 to 60 degrees c, relative humidity type 0 to 1 volt for 0 to 100 percent rh; measurement of air dewpoint achieved by opto-electronic detection of dew formed on an electrically cooled, solid gold mirror, the temp of mirror is continually monitored and when dew forms the temp is stored in memory; probe houses the dew forming mirror and optics, also carries another transducer for measuring ambient temp; operates and displays continuously while cycling through dewpoint determination every 1/2 to 2 minutes; item will be used to maintain accuracy of the following systems-t.O. 33k6-4-2024-1, p/n 31061222-001, t.O. 33k5-4-84-1 p/n's ct428-7, rh200, htab176

**Functional Description:**

The protimeter dewpoint meter uses analog and digital electronics to simplify accurate and stable hygrometric measurement; direct measurement of dewpoint temperature

**Reference Data And Literature:**

T.O. 33k1-1-100

**Relationship To Similar Equipment:**

Replaces the air force's current temp and humidity transfer standards used in pmel, p/n sa-760-a nsn 6625-01-144-1855 digital readout and p/n h5-3552-b (nsl) humidity probe

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A27600