

View Online at <https://aerobasegroup.com/nsn/6685-01-437-3644>

Overall Depth:

1.953 inches

Overall Diameter:

2.750 inches

Case Material:

Steel, alloy

Case Surface Treatment:

Enamel, black

Graduation Unit:

100.0 kilograms per square centimeter and 10.0 pounds per square inch

Actuation Type:

Bourdon tube

Adjustability:

Nonadjustable

Scale Range:

+0.0/+700.0 kilograms per square centimeter and +0.0/+100.0 pounds pressure per square inch

Scale Name:

Kilopascals and pounds pressure

Dial Size:

2.5 in. Dia.

Connection Quantity:

1

Pointer Color:

Black

Pointer Type:

Indicating

Scale Type:

Dial

Scale Smallest Increment:

20.0 kilograms per square centimeter and 2.0 pounds

Connection Type:

External

Mounting Method:

Rigid stem

Scale Accuracy:

Amse b 40.1 grade b, +/- 3-2-3 percent

Actuating Element Material:

Beryllium copper

Scale Name For Which Pointer Is Designed:

Kilopascals and pounds pressure

Connection Location:

Back, center

Bezel Type:

Crimp

Connection Size:

1/4 in. Npt

Mounting Connection Location:

Back, center

Connector Type Vent:

Not provided

Special Features:

Used on f-16 munitions traine (block 50)

Surface Treatment:

Aluminum alloy

Surface Treatment:

Aluminum, dull

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

T179-b