Dial Indicating Pressure Gage - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6685-01-493-5324

Graduation Unit: 500.0 pounds per square inch Actuation Type: Bourdon tube Adjustability: Nonadjustabile Scale Range: +0.0/+3000.0 pounds pressure per square inch Scale Range: +0.0/+3000.0 pounds pressure per square inch Scale Name: Pounds pressure Pointer Color: Any acceptable Pointer Type: Dial Scale Smallest Increment: 100.0 pounds per square inch Connection Type: External Mounting Method: Threaded male connection Actuating Element Material: Steel, stainless Connection Size: 0.250npt Co		
Actuation type: Bourdon tube Adjustability: Nonadjustable Scale Range: +0.0/+3000.0 pounds pressure per square inch Scale Name: Pounds pressure Daid Size: 4.5in Connection Quantity: 1 Pointer Color: Any acceptable Pointer Type: Indicating Scale Smallest Increment: 10.0.0 pounds per square inch Connection Type: Dial Scale Smallest Increment: 10.0.0 pounds per square inch Connection Type: External Mounting Method: Threaded male connection Actuating Element Material: Steel, stainless Connection Location: Lower Oxonection Size: 0.250npt Connector Type Vent: Nat provided Shelf Life: Nid Dird Measure: - Piner Color: Steel, Steil Life: Nid	Graduation Unit:	
Bourdon tube Adjustability: Nonadjustable Scale Range: +0.0/+3000.0 pounds pressure per square inch Scale Name: Pounds pressure Pounds pressure Dial Size: 4.5in Connection Quantity: 1 Pointer Type: Indicating Scale Type: Dial Scale Smallest Increment: 100.0 pounds per square inch Connection Type: External Mounting Method: Threaded male connection Actuating Element Material: Steel, stainless Connection Size: Augument Consument Consust Consument Consument Consument Consument Consument Consust	500.0 pounds per square inch	
Adjustability:NonadjustabileScale Range:+0.0/+3000.0 pounds pressure per square inchScale Name:Pounds pressureDauds pressureDial Size:4.5inConnection Quantity:1Pointer Color:Any acceptablePointer Type:IndicatingScale Type:DialScale Smallest Increment:100.0 pounds per square inchConnection Type:ExternalMounting Method:Threaded male connectionActuating Element Material:Steel, stainlessConnection Size:0.250nptStepl Type Vent:Nat providedShelf Life:NatDialStepl Stepl Size:Stepl Size:Onnection Size:0.250nptNat providedShelf Life:NaDialStepl Size:Stepl Size: <th>Actuation Type:</th> <th></th>	Actuation Type:	
Nonadjustable Scale Range: +0.0/+3000.0 pounds pressure per square inch Scale Name: Pounds pressure Pounds pressure Dial Size: 4.5in Connection Quantity: 1 Pointer Color: Any acceptable Pointer Type: Indicating Scale Type: Dial Scale Smallest Increment: 100.0 pounds per square inch Connection Type: External Mounting Method: Threaded male connection Actuating Element Material: Steel, stainless Connection Size: 0.250npt Not provided Shelf Life: N/a Diat Of Measure: To Pointer Type Vent: Not provided Shelf Life: N/a Diation Measure: To Pointer Type Vent: Not provided Shelf Life: N/a Diation Measure:	Bourdon tube	
xue xue xue xue Pounds pressure xue Dial Size: xue 4.5in xue Connection Quantity: xue 1 Xue Pointer Color: xue Any acceptable Xue Pointer Type: xue Indicating Xue Scale Smallest Increment: Xue 100.0 pounds per square inch Xue Connection Type: Xue Xue Xue <td< th=""><th>Adjustability:</th><th></th></td<>	Adjustability:	
+0.0/+3000.0 pounds pressure per square inchScale Name:Pounds pressureDial Size:4.5inConnection Quantity:1Pointer Color:Any acceptablePointer Type:IndicatingScale Type:DialScale Smallest Increment:100.0 pounds per square inchConnection Type:ExternalMounting Method:Threaded male connectionActuating Element Material:Steel, stainlessConnection Size:0.250nptConnector Type Vent:Not providedShelf Life:NaUnit Of Measure:Demilitarization:NoFig:Fig:	Nonadjustable	
Scale Name: Pounds pressure Pounds pressure Dial Size: 4.5in Connection Quantity: 1 Pointer Color: Any acceptable Pointer Type: Indicating Scale Type: Indicating Scale Type: Dial Scale Smallest Increment: 100.0 pounds per square inch Connection Type: External Mounting Method: Threaded male connection Actuating Element Material: Steel, stainless Connection Size: D.250npt Connector Type Vent: Not provided Sheff Life: Na Unit Of Measure: T Demilitarization: No Fig:	Scale Range:	
Pounds pressure Dial Size: 4.5in 4.5in Connection Quantity: 1 Pointer Color: Any acceptable Pointer Type: Indicating Scale Type: Indicating Scale Type: Indicating Scale Smallest Increment: 100.0 pounds per square inch Connection Type: External Mounting Method: Threaded male connection Actuating Element Material: Steel, stainless Connection Size: Icower Connection Size: Icoyent Connector Type Vent: Not provided Sheff Life: Na Unit Of Measure: Ico Dailon	+0.0/+3000.0 pounds pressure per square inch	
Dial Size: 4.5in Connection Quantity: 1 Pointer Color: Any acceptable Pointer Type: Indicating Scale Type: Dial Scale Smallest Increment: 100.0 pounds per square inch Connection Type: External Mounting Method: Threaded male connection Actuating Element Material: Steel, stainless Connection Size: Lower Connector Type Vent: Not provided Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Scale Name:	
4.5in Connection Quantity: 1 Pointer Color: Any acceptable Pointer Type: Indicating Scale Type: Dial Scale Smallest Increment: 100.0 pounds per square inch Connection Type: External Mounting Method: Threaded male connection Actuating Element Material: Steel, stainless Connection Location: Lower Connection Size: 0.250npt Connector Type Vent: Nd provided Sheff Life: N/a Unit of Measure: Demilitarization: No Fig:	Pounds pressure	
Connection Quantity: 1 Pointer Color: Any acceptable Pointer Type: Indicating Scale Type: Dial Scale Smallest Increment: 100.0 pounds per square inch Connection Type: External Mounting Method: Threaded male connection Actuating Element Material: Steel, stainless Connection Location: Lower Connection Size: 0.250npt Connector Type Vent: Not provided Sheff Life: N/a Unit Of Measure: Demilitarization: No Fig:	Dial Size:	
1 Pointer Color: Any acceptable Pointer Type: Indicating Scale Type: Dial Scale Smallest Increment: 100.0 pounds per square inch Connection Type: External Mounting Method: Threaded male connection Actuating Element Material: Steel, stainless Connection Size: 0.250npt Connector Type Vent: Not provided Shelf Life: Na Unit Of Measure: - Pomilitarization: No Fig:	4.5in	
Pointer Color: Any acceptable Pointer Type: Indicating Scale Type: Dial Scale Smallest Increment: 100.0 pounds per square inch Connection Type: External Mounting Method: Threaded male connection Actuating Element Material: Steel, stainless Connection Location: Lower Connection Size: 0.250npt Connecton Size: 0.250npt Connector Type Vent: Not provided Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Connection Quantity:	
Any acceptable Pointer Type: Indicating Scale Type: Dial Scale Smallest Increment: 100.0 pounds per square inch Connection Type: External Mounting Method: Threaded male connection Actuating Element Material: Steel, stainless Connection Location: Lower Connection Size: 0.250npt Connector Type Vent: Not provided Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	1	
Pointer Type:IndicatingScale Type:DialScale Smallest Increment:100.0 pounds per square inchConnection Type:ExternalMounting Method:Threaded male connectionActuating Element Material:Steel, stainlessConnection Location:LowerConnector Type Vent:Not providedShelf Life:NdaUnit Of Measure:-Pemilitarization:NoFig:	Pointer Color:	
Indicating Scale Type: Dial Scale Smallest Increment: 100.0 pounds per square inch Connection Type: External Mounting Method: Threaded male connection Actuating Element Material: Steel, stainless Connection Location: Lower Connection Size: 0.250npt Connector Type Vent: Not provided Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Any acceptable	
Scale Type: Dial Scale Smallest Increment: 100.0 pounds per square inch Connection Type: External Mounting Method: Threaded male connection Actuating Element Material: Steel, stainless Connection Location: Lower Connection Size: 0.250npt Connector Type Vent: Not provided Shelf Life: N/a Unit Of Measure: - - Demilitarization: No	Pointer Type:	
Dial Scale Smallest Increment: 100.0 pounds per square inch Connection Type: External Mounting Method: Threaded male connection Actuating Element Material: Steel, stainless Connection Location: Lower Connection Size: 0.250npt Connector Type Vent: Not provided Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Indicating	
Scale Smallest Increment: 100.0 pounds per square inch Connection Type: External Mounting Method: Threaded male connection Actuating Element Material: Steel, stainless Connection Location: Lower Connection Size: 0.250npt Connector Type Vent: Not provided Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Scale Type:	
100.0 pounds per square inch Connection Type: External Mounting Method: Threaded male connection Actuating Element Material: Steel, stainless Connection Location: Lower Connection Size: 0.250npt Connector Type Vent: Not provided Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Dial	
Connection Type: External Mounting Method: Threaded male connection Actuating Element Material: Actuating Element Material: Steel, stainless Connection Location: Lower Connection Size: O.250npt Connector Type Vent: Not provided Shelf Life: N/a Unit Of Measure: Demilitarization: No	Scale Smallest Increment:	
External Mounting Method: Threaded male connection Actuating Element Material: Steel, stainless Connection Location: Lower Connection Size: O.250npt Connector Type Vent: Not provided Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	100.0 pounds per square inch	
Mounting Method: Threaded male connection Actuating Element Material: Steel, stainless Connection Location: Lower Connection Size: 0.250npt Connector Type Vent: Not provided Shelf Life: N/a Unit Of Measure: Pemilitarization: No	Connection Type:	
Threaded male connection Actuating Element Material: Steel, stainless Connection Location: Lower Connection Size: O.250npt Connector Type Vent: Not provided Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	External	
Actuating Element Material: Steel, stainless Connection Location: Lower Connection Size: 0.250npt Connector Type Vent: Not provided Shelf Life: N/a Unit Of Measure: Demilitarization: No	Mounting Method:	
Steel, stainless Connection Location: Lower Connection Size: 0.250npt Connector Type Vent: Not provided Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Threaded male connection	
Connection Location: Lower Connection Size: 0.250npt Connector Type Vent: Not provided Shelf Life: N/a Unit Of Measure: Demilitarization: No	Actuating Element Material:	
Lower Connection Size: 0.250npt Connector Type Vent: Not provided Shelf Life: N/a Unit Of Measure: No Fig:	Steel, stainless	
Connection Size: 0.250npt Connector Type Vent: Not provided Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Connection Location:	
0.250npt Connector Type Vent: Not provided Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Lower	
Connector Type Vent: Not provided Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Connection Size:	
Not provided Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.250npt	
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Connector Type Vent:	
N/a Unit Of Measure: Demilitarization: No Fiig:	Not provided	
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:	
 Demilitarization: No Fiig:	N/a	
No Fiig:	Unit Of Measure:	
No Fiig:		
Fiig:	Demilitarization:	
	No	
	Fiig:	