

View Online at <https://aerobasegroup.com/nsn/6685-01-525-3300>

Overall Depth:

83.0 millimeters

Mounting Hole Quantity:

3

Overall Diameter:

131.0 millimeters

Case Material:

Steel, corrosion resisting

Graduation Unit:

500.0 pounds per square inch

Actuation Type:

Bourdon tube

Adjustability:

Nonadjustable

Scale Range:

+0.0/+3000.0 pounds per square inch

Scale Name:

Pounds pressure and kilopascals

Dial Size:

100.0 millimeter nom. Diameter

Connection Quantity:

1

Pointer Color:

Black

Pointer Type:

Indicating

Scale Type:

Dial

Scale Smallest Increment:

50.0 pounds per square inch

Connection Type:

External

Mounting Method:

Flange

Scale Accuracy:

1.6 percent of full scale

Actuating Element Material:

Steel, corrosion resisting

Scale Inscription/background Color:

White aluminum with black lettering

Scale Name For Which Pointer Is Designed:

Kilopascals and pounds pressure

Connection Location:

Back, lower

Bezel Type:

Bayonet

Protective Crystal Material:

Laminated glass

Connection Size:

0.250 inch npt diameter

Connector Type Vent:

Not provided

Product Name:

Model 656 stainless steel pressure gauges

Special Features:

Dial also has kilopascals (kpa) scale markings - minor 500.0 kpa, intermediate 1000.0 kpa, major with numbers 5000.0; mounting connection front flange; corrosion resistant steel is 316l material; working pressure 50.0 percent of full scale; over range protection is 125.0 percent of full scale; working temperature minus 40.0 to plus 60.0 degrees c; bourdon tube is helical type; case pressure relief rubber disc location back of case; no fill; oxygen cleaned

Material:

Steel, corrosion resisting

Material:

Stainless steel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T179-b