NSN 6685-01-526-1709

U-tube Manometer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6685-01-526-1709

| Maximum Operating Pressure: |
|---|
| 10.7 pounds per square inch |
| Mounting Type: |
| Carrying case |
| Accessory Components And Quantity: |
| Series 475-fm manometer 1, a303static pressure tips 2, 9 ft 3/8 inch id rubber tube 2, 66-6 cf pitot tube 1, a397drill 1, a532 air veloci type 1, |
| slide chart 1, instruction sheet h-11-1 |
| Usage Design: |
| Maintain air protective cover eglin an/fps-85 radar |
| Zero Adjuster: |
| Provided |
| Connection Type: |
| Threaded |
| Connection Facility Type: |
| External |
| Connection Location: |
| Тор |
| Product Name: |
| 475-av air velocity kit |
| Special Features: |
| Handheld, air velocity gage, rugged plastic case, .5 in 3.5 digit display, safely used in hazardous location, class1, div 1, grp a, b, c, d t4, |
| accuracy p/m.5%, operating temp 0-140 degrees f, req 9v battery, 2 barbed connection 1/8 or 16 inch id tubing, h 7.5 inch, w 3 inch, 0.5 inch |
| liq crystal, 10.8 ounces |
| Functional Description: |
| Field calibration low pressure pneumatic systems i.E.Hvac, clean rooms.Vacumm systems |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| T179-d |
| |