

View Online at <https://aerobasegroup.com/nsn/6685-01-573-6135>

**Width:**

14.400 inches

**Ac Voltage Rating:**

Between 85.0 volts and 250.0 volts

**Frequency Rating:**

Between 50.0 hertz and 60.0 hertz

**Depth:**

14.000 inches

**End Application:**

Gpete

**Presentation Type:**

Digital display

**Individual Marking:**

Display screen: standard used (its-90 or ipts-68); instrument mode (source or meter); thermocouple type connectors used (binding posts or thermocouple connector); input/output of temperature or voltage; reference-junction temperature (deg f, degrees c, k, or degrees r); offset in degrees or voltage; wire type used (copper or alloy)

**Display Type:**

Liquid crystal

**Display Digit Quantity:**

8

**Product Name:**

Inavy: simulator-calibrator; cage: thermocouple simulator-calibrator

**Special Features:**

accuracy: 0.06 degrees c for common thermocouple types; simulates and measures thermocouples; sources and measures dc microvolts to volts; dc accuracy: 0.0025 pc plus 2.0uv for 6 months; output impedance: 0.05 ohm, all ranges; gpib interface included (ethernet, rs-232, and usb optional); up to 31 memories for storing preset conditions; ramp for linearity testing; programmable; supports scpi commands

**Height:**

3.500 inches

**Supplementary Features:**

Front panel has display panel; 12-key keypad; menu, enter, and esc keys, 4 arrow keys; ac power push button; encoder knob; 3 binding post connectors; 1 thermocouple connector; has instrument bail/retractable stand on bottom

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A533y0