

View Online at <https://aerobasegroup.com/nsn/6695-00-320-8312>

Diameter:

0.375 inches

Length:

1.156 inches

Mounting Slot Width:

0.125 inches

Mounting Slot Length:

0.445 inches

Current Type:

Dc

Dc Voltage Rating:

Between 22.0 volts and 30.0 volts

Distance Between Mounting Facility Centers:

0.686 inches

Contact Quantity:

3

End Application:

Nsns 6680-00-593-3306 and 6680-00-790-0082 liquid oxygen indicator sets tech order 15x4-3-1-114

Contact Type:

Terminal lug

Presentation Type:

Drum dial and window

Mounting Arrangement Style:

Two hole/stud

Marking Color Specificationific Use:

Power-off signal and power-on signal

Mounting Facility Type And Quantity:

2 slotted hole

Case Material:

Steel

Dial Outside Diameter:

0.385 inches

Special Features:

Operating time 0.1 second or less; coil resistance 750 ohms; indicator case tin-plated for corrosion resistance; operating temp range minus 55 degrees c to 90 degrees c; insulation resistance 20 meg. Ohms at 500 volts dc winding to case; high potential requirements-each unit can withstand 500 volts ac at 60 hz p.S. For 15 seconds

Height:

0.380 inches

Supplementary Features:

Indicator energized position background position lusterless black color no. 37038; indicator de-energized position (off) characters lusterless white color no. 37875 on red background color no. 31158; word off is 0.094 in. High; back surface to be free of paint

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fig:

A534r0