

View Online at <https://aerobasegroup.com/nsn/6695-00-320-8312>

**Diameter:**

0.375 inches

**Length:**

1.156 inches

**Mounting Slot Width:**

0.125 inches

**Mounting Slot Length:**

0.445 inches

**Current Type:**

Dc

**Dc Voltage Rating:**

Between 22.0 volts and 30.0 volts

**Distance Between Mounting Facility Centers:**

0.686 inches

**Contact Quantity:**

3

**End Application:**

Nsns 6680-00-593-3306 and 6680-00-790-0082 liquid oxygen indicator sets tech order 15x4-3-1-114

**Contact Type:**

Terminal lug

**Presentation Type:**

Drum dial and window

**Mounting Arrangement Style:**

Two hole/stud

**Marking Color Specificationific Use:**

Power-off signal and power-on signal

**Mounting Facility Type And Quantity:**

2 slotted hole

**Case Material:**

Steel

**Dial Outside Diameter:**

0.385 inches

**Special Features:**

Operating time 0.1 second or less; coil resistance 750 ohms; indicator case tin-plated for corrosion resistance; operating temp range minus 55 degrees c to 90 degrees c; insulation resistance 20 meg. Ohms at 500 volts dc winding to case; high potential requirements-each unit can withstand 500 volts ac at 60 hz p.S. For 15 seconds

**Height:**

0.380 inches

**Supplementary Features:**

Indicator energized position background position lusterless black color no. 37038; indicator de-energized position (off) characters lusterless white color no. 37875 on red background color no. 31158; word off is 0.094 in. High; back surface to be free of paint

**Shelf Life:**

N/a

**Unit Of Measure:**

**Demilitarization:**

No

**Fig:**

A534r0