Photographic Contact Printer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6740-00-723-4582

Mounting T	/pe·
Table	ihe.
	~~~~
Overall Ler	
Overall Hei	
31.000 inch Overall Wid	
21.000 inch	
Current Ty	e:
Ac	
Frequency	
	0 hertz and 60.0 hertz
Lamp Quar	lity:
1	
	ge Rating In Watts:
200.0	
Lamp Type	
Incandesce	
Carrying Car	se:
Provided	
Furnished	tems And Quantity:
Adapter 10,	cord 1, projection lamp 4
Printer Typ	*:
Continuous	
Voltage Ra	ing:
115.0 volts	
Platen Type	:
Pressure	
Material Ty	be For Which Designed:
Roll film or r	bll paper
Color Print	ng Feature:
Provided	
Variable Co	ntrast Paper Printing Accessory:
Filter	
Safelight La	mp Quantity:
2	
Safelight La	тр Туре:
Fluorescent	
Safelight La	mp Wattage In Watts:
10.0	
Scanning L	amp Quantity:
2	

Photographic Contact Printer - Page 2 of 2



Scanning Lamp Type: Incandescent Scanning Lamp Wattage In Watts: 15.0 Phase: Single **Special Features:** Max size 9.5 in. W, 500 ft lg, print speed 60 ft per min Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: Т150-е