

View Online at <https://aerobasegroup.com/nsn/6760-00-083-0363>

Functional Classification:

Aa-9.1

Functional Description:

Used to select, route, and measure output signal voltage of aircraft camera control system

Entry Date:

71-02-28

Reference Data And Literature:

Tm11-6760-220-12, tm11-6760-220-20p, tm11-6760-220-45/1, tm11-6760-220-45/2, tm11-6760-220-45/3, tm11-6760-220-45/4, tm11-6760-220-45p/2, tm11-6760-220-45p/1, tm11-6760-220-45p/3, tm11-6760-220-45p/4

Relationship To Similar Equipment:

Similar to ls-35 which it replaces

General Description:

M15.125 in. L, 15.125 in. W, 18.500 in. H, 115 vac and 28 vdc input voltage, 400 hz input frequency, single phase, 28.75 watts ac and 280 watts dc input power consumption, type test performed-voltage measurement, type indication-meter, continuous-running motor clutch controlled w/0 to 60 sec range graduated in increments of 0.01 sec to 1 sec-timer clock output, d'arsonal movement 50 microampere sensitivity direct reading in go or no-go graduations-type condition meter output

Type/model Designation:

Ls-35a

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli