

View Online at <https://aerobasegroup.com/nsn/6760-00-240-3090>

**Special Features:**

60 mf p 15 m 10 pct condenser cap.; elec 28v dc; 1 inverter 7 amp output rating; maj comp 1 ea bendix aviation corporation mtr alternater p/n 115-5267p2, raytheon mfg co transformer p/n u8741d, ge co flash tube p/n 77-5032p1, raytheon mfr co chassis p/n 29-514g1; 1 flash tube ge co type ft-24 1000 flashes approx life, flash tube incl; 3 every 1 sec maximum flashing rate; 300 ft effective altitude; components are provisioned for individual mtg or suspension in aircraft; 118; 5 lb wt of complete complete assembly; feat ventilated al cover, special neoprene covering on cables, trigger switch needs 5 sec preheating, automatic or semiautomatic operation; designed for p2v-2, p2v-3, p2v-4, tbm-38 and pbm-55 type aircraft; u/w type k-25a and k-25b cameras; govt type buaer, flasher unit, type f2a-1a

**General Description:**

60 mf p 15 m 10 pct condenser cap.; elec 28v dc; 1 inverter 7 amp output rating; maj comp 1 ea bendix aviation corporation mtr alternater p/n 115-5267p2, raytheon mfg co transformer p/n u8741d, ge co flash tube p/n 77-5032p1, raytheon mfr co chassis p/n 29-514g1; 1 flash tube ge co type ft-24 1000 flashes approx life, flash tube incl; 3 every 1 sec maximum flashing rate; 300 ft effective altitude; components are provisioned for individual mtg or suspension in aircraft; 118; 5 lb wt of complete complete assembly; feat ventilated al cover, special neoprene covering on cables, trigger switch needs 5 sec preheating, automatic or semiautomatic operation; designed for p2v-2, p2v-3, p2v-4, tbm-38 and pbm-55 type aircraft; u/w type k-25a and k-25b cameras; govt type buaer, flasher unit, type f2a-1a

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A23900