

View Online at <https://aerobasegroup.com/nsn/6760-00-240-7437>

Special Features:

100 uf condenser cap.; elec 115, 24v ac, dc; maj comp 1 ea raytheon mfg co transformer p/n t-2, condenser p/n 2f-320, flash tube p/n 277-1016p1, chassis p/n 29-5140g1; accessories 1 ea tube, v regulator, trigger, rectifier, flash; 1 flash tube ge co p/n ft524 10000 flashes approx life, flash tube incl; 3 every 1 sec maximum flash rate; 150 ft effective altitude; components are provisioned for mtg or suspending in aircraft; 118.5 lb wt of comp assembly; feat special 50 ft cables req pwr lines grounded externally 400 cycles 3 phase operation; aircraft for which designed a/a; u/w type k-25a camera; govt type buaer, flash tube unit, type f2a-2

General Description:

100 uf condenser cap.; elec 115, 24v ac, dc; maj comp 1 ea raytheon mfg co transformer p/n t-2, condenser p/n 2f-320, flash tube p/n 277-1016p1, chassis p/n 29-5140g1; accessories 1 ea tube, v regulator, trigger, rectifier, flash; 1 flash tube ge co p/n ft524 10000 flashes approx life, flash tube incl; 3 every 1 sec maximum flash rate; 150 ft effective altitude; components are provisioned for mtg or suspending in aircraft; 118.5 lb wt of comp assembly; feat special 50 ft cables req pwr lines grounded externally 400 cycles 3 phase operation; aircraft for which designed a/a; u/w type k-25a camera; govt type buaer, flash tube unit, type f2a-2

Specification Or Standard:

F2a-2 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A23900