

View Online at <https://aerobasegroup.com/nsn/6760-00-240-7437>

**Special Features:**

100 uf condenser cap.; elec 115, 24v ac, dc; maj comp 1 ea raytheon mfg co transformer p/n t-2, condenser p/n 2f-320, flash tube p/n 277-1016p1, chassis p/n 29-5140g1; accessories 1 ea tube, v regulator, trigger, rectifier, flash; 1 flash tube ge co p/n ft524 10000 flashes approx life, flash tube incl; 3 every 1 sec maximum flash rate; 150 ft effective altitude; components are provisioned for mtg or suspending in aircraft; 118.5 lb wt of comp assembly; feat special 50 ft cables req pwr lines grounded externally 400 cycles 3 phase operation; aircraft for which designed a/a; u/w type k-25a camera; govt type buaer, flash tube unit, type f2a-2

**General Description:**

100 uf condenser cap.; elec 115, 24v ac, dc; maj comp 1 ea raytheon mfg co transformer p/n t-2, condenser p/n 2f-320, flash tube p/n 277-1016p1, chassis p/n 29-5140g1; accessories 1 ea tube, v regulator, trigger, rectifier, flash; 1 flash tube ge co p/n ft524 10000 flashes approx life, flash tube incl; 3 every 1 sec maximum flash rate; 150 ft effective altitude; components are provisioned for mtg or suspending in aircraft; 118.5 lb wt of comp assembly; feat special 50 ft cables req pwr lines grounded externally 400 cycles 3 phase operation; aircraft for which designed a/a; u/w type k-25a camera; govt type buaer, flash tube unit, type f2a-2

**Specification Or Standard:**

F2a-2 type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A23900