

View Online at <https://aerobasegroup.com/nsn/6760-01-407-5291>

Mounting Provision:

Slip-on

Overall Depth:

4.000 inches

Overall Height:

5.300 inches

Overall Width:

3.100 inches

Current Type:

Dc

Specific Use:

Still picture camera

Actuation Method:

Electronic shutter

Voltage Rating:

6.0 pounds per hour wet

Mounting Characteristic:

Mounted

Synchronization Feature:

Included

Flash Media For Which Designed:

Repeating flash unit

Special Features:

3d multi-sensor balanced fill-flash w/monitor pre-flashes (n90, n70, and d-type af nikkor); multi-sensor balanced fill-flash w/monitor pre-flashes (n90, n70, cpu lens, except d-type af nikkor); matrix balanced fill-flash (f4, n8008s, n6006, n50, and cpu lens); slow sync (n90, n70, or n6006); rear curtain sync (f4, n90, n8008, n70, n6006); red-eye reduction (n90, n70); fp high-speed sync (n90); af-assist illuminator for af slr; repeating flash; manual flash level compensation; wireless slave flash; automatic power zoom coverage 24mm to 85mm (f4, n90, n8008, n70, cpu lens); 18mm built-in wide flashadapter; built-in bounce card; tilting/rotating flash head; lcd panel w/illumination; recycling time 7 sec; uses aa batteries or battery pack; soft caseincluded; this is a multimedia item for authorized users on ta 629aaoo only

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T150-f