NSN 6930-00-500-6902

Indicator Simulated - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6930-00-500-6902

End Application:

Trainer flight simulator, a/f37a-t49, f-15a aircraft; 6930003220829

Special Features:

Indicator shall duplicate those of the operational indicator, indicated airspeed, avu-19/a, standby, aerosonic corporation p/n 25085-1103, to include the same visual appearance, frictional feel and movement; single servo type; one scale, marked-usaf avu-19/a, airspeed, knots x 100; scale range 0 to 850 knots, calibrated 10 knots per increment to 200 knots, 50 knots per increment to 850 knotsl letters, lined increments and numerals are non-luminous, white-lusterless; one elec connector, deutsch type, p/n 5605-3p; 2 mechanical connects, size 1/4 in nom, boss type; red and white integral pointer, non-luminous white-lusterless; , panel mounted; nom sz 2 in; case dim 2.375 in nom lg, 2.375 in nom wd.4.438 in maximum dp; pwr rqmts; 115 vac, 400 hz; oper temp rg-40 degrees f to 120 degrees f; an indicator calibrated in units of velocity indicating forward velocity with respect to the surrounding air mass; simulates aaerosonic corporation indicated airspeed indicator, standby; type no.Avu-19; p/n 28085-1103

Reference Number Differentiating Characteristics:

As differentiated by source control drawing number

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A532m0