

View Online at <https://aerobasegroup.com/nsn/7010-01-329-6361>

Alternating Current Voltage Rating In Volts:

120.0

Indicator Type:

Liquid crystal display

Power Source:

External or self-contained

Input Intelligence Type:

Digital

Intelligence Input Method:

Electrical

Output Intelligence Type:

Digital

Phase:

Single

Special Features:

Rugged hand-held computer (rhc-88p/n 9900-01923-0009) modified; nha is martin marietta p/n 717705010-009, transit case assembly-portable data terminal (pdt); download process is via a modem and dual rs-232 interface splitter which is part of nnha p/n 717705016-009, kit-pdt; consists of screen and keyboard; includes 120 vac adapter, ni-cd battery pack, utilities disk, 1 megabyte eprom, 512 kilobyte ram pcb kit 2 data cables, process pcb, video pcb assembly, frequency panel assembly and 2 user manuals; used in support of the lantirn mobile shelter station

Frequency In Hertz:

60.0

Functional Description:

Wused to collect data from the navigational and target pods via the data logging modules located on the advanced log fire control computer located on the aircraft; data is downloaded and saved on a pc or mainframe for data analysis

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A30800