

View Online at <https://aerobasegroup.com/nsn/7025-01-476-9540>

End Application:

Launching accessories

Unit Design:

Panel mounted

Criticality Code Justification:

Agav

Product Name:

Display, flat panel

Input Device Type:

Keyboard

Output Device Type:

Liquid crystal

Special Features:

This unit includes 16 mbytes dram , floppy disk controller: keyboard port (pc at connector), 640h x 480v video controller; vga (16 color), svga (256 color) compatible, at compatible bios 25 mhz clock frequency , 32.0 mbytes on-board solid state disk (flash technologies, disk on chip, two ibm compatible serial ports; 1) com1, 3f8h, irq4 (controls touch panel), com2, 2f8h, irq3, parallel printer port; lpt1, 378h, irq7, real time clock with battery backup, ibm pc bus (and/or pc104), 48 port digital i/o card pcm-uio48 or exact functional equivalent (base 0x300h, irq5), . Computer shall come with dos 6.22 or higher installed in flash and 3429as9046 software installed., two opto-isolated rs 422/485 ports: 1) ch1, 2e8h, irq9 (j15, com3); 2) ch2, 3e8h, irq11 and a lcd touch screen. unit is 12.96 inches in length x 10.855inches in height x 5.00 inches deep not including mounting flange or ports sticking out of the back.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A507b0