NSN 7025-01-480-2728

Automatic Data Processing Printer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/7025-01-480-2728

Overall Height:
22.000 inches
Overall Width:
26.000 inches
Printer Type:
Thermal
Features Provided:
Color capable and changeable fonts and expandable buffer memory
Unit Design:
Free standing
Interface Type:
Scsi
Special Features:
Requested name fuji pictrography; silver halide photographic process combined with Id exposure and thermal development and transfer;
$256 \; density \; levels \; eacg \; for \; y, \; \; m \; and \; c \; - \; total \; of \; 16.7 \; million \; color \; shades; \; recording/pixel \; desity \; - \; 400dp \; (15.7 \; dots/mm) \; 4709 \; x \; 3431 \; pixels \; density \; - \; 400dp \; (15.7 \; dots/mm) \; 4709 \; x \; 3431 \; pixels \; density \; - \; 400dp \; (15.7 \; dots/mm) \; 4709 \; x \; 3431 \; pixels \; density \; - \; 400dp \; (15.7 \; dots/mm) \; 4709 \; x \; 3431 \; pixels \; - \; 400dp \; (15.7 \; dots/mm) \; 4709 \; x \; 3431 \; pixels \; - \; 400dp \; (15.7 \; dots/mm) \; 4709 \; x \; 3431 \; pixels \; - \; 400dp \; (15.7 \; dots/mm) \; 4709 \; x \; 3431 \; pixels \; - \; 400dp \; (15.7 \; dots/mm) \; 4709 \; x \; 3431 \; pixels \; - \; 400dp \; (15.7 \; dots/mm) \; 4709 \; x \; 3431 \; pixels \; - \; 400dp \; (15.7 \; dots/mm) \; 4709 \; x \; 3431 \; pixels \; - \; 400dp \; (15.7 \; dots/mm) \; 4709 \; x \; 3431 \; pixels \; - \; 400dp \; (15.7 \; dots/mm) \; 4709 \; x \; 3431 \; pixels \; - \; 400dp \; (15.7 \; dots/mm) \; 4709 \; x \; 3431 \; pixels \; - \; 400dp \; (15.7 \; dots/mm) \; 4709 \; x \; 3431 \; pixels \; - \; 400dp \; (15.7 \; dots/mm) \; 4709 \; x \; 3431 \; pixels \; - \; 400dp \; (15.7 \; dots/mm) \; 4709 \; x \; 3431 \; pixels \; - \; 400dp \; (15.7 \; dots/mm) \; 4709 \; x \; 3431 \; pixels \; - \; 400dp \; (15.7 \; dots/mm) \; 4709 \; x \; 3431 \; pixels \; - \; 400dp \; (15.7 \; dots/mm) \; 4709 \; x \; 3431 \; pixels \; - \; 400dp \; (15.7 \; dots/mm) \; 4709 \; x \; 3431 \; pixels \; - \; 400dp \; (15.7 \; dots/mm) \; 4700 \; pixels \; - \; 400dp \; (15.7 \; dots/mm) \; 4700 \; pixels \; - \; 400dp \; (15.7 \; dots/mm) \; 4700 \; pixels \; - \; 400dp \; (15.7 \; dots/mm) \; 4700 \; pixels \; - \; 400dp \; (15.7 \; dots/mm) \; 4700 \; pixels \; - \; 400dp \; (15.7 \; dots/mm) \; 4700 \; pixels \; - \; 400dp \; (15.7 \; dots/mm) \; 4700 \; pixels \; - \; 400dp \; (15.7 \; dots/mm) \; 4700 \; pixels \; - \; 400dp \; - \; $
max; 30mb or 48mb frame memory; scsi or gpib (hp-ib) interface; dimensions - 26"w x 22"d x 22"h; 7a or 12a max. Current consumption;
120v, 60hz or 220-240vac, 50/60hz; printing time - 2 minute ffirst print, 70 seconds subsequent prints in continuous operation; this is a
multimedia item for authorized users on ta 629aaoo only
Type/model Designation:
Pictrography 3000
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A506k0