

View Online at <https://aerobasegroup.com/nsn/7025-01-485-1931>

**Mounting Type:**

Base

**Alternating Current Voltage Rating In Volts:**

100.0 and 240.0

**Storage Temperature Range:**

-13.0/+158.0 degrees fahrenheit

**End Application:**

Control, whidbey island class lsd

**Unpackaged Unit Length:**

5.30 inches

**Unpackaged Unit Width:**

10.00 inches

**Unpackaged Unit Height:**

1.40 inches

**Power Source:**

External

**Phase:**

Single

**Special Features:**

I-2 fiber-optic ports for sc, mt-rj, or vf-45, 6-7 tx ports with auto-negotiation 10/100mbps, auto-negotiation for speed and duplexity on tx ports, rear dip switch to force one fx port to half or full duplex, rear dip switches to force one tx port to half or full duplex and 10 or 100mbps, true non-blocking architecture, store-and-forward mechanism, back pressure and ieee 802.3x compliant flow control, supports 1k mac addresses, one uplink port, front panel port utilization and status leds, wall-mountable compact size

**Frequency In Hertz:**

50.0 and 60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A30800