

View Online at <https://aerobasegroup.com/nsn/7025-01-504-9811>

Mounting Type:

Bracket

Direct Current Voltage Rating In Volts:

7.0 and 32.0

End Application:

6625-01-445-0085

Unpackaged Unit Length:

2.75 inches

Unpackaged Unit Width:

5.11 inches

Unpackaged Unit Height:

1.25 inches

Power Source:

External

Special Features:

Hardware features: reverse voltage protection, on-board flash for field upgrades, leds indicating pc and network status, rs-232 driver capable of 230k baud, ce certification (emc), protocols supported: dpa ii plus: can, j1939, j1708, j1587, j1922, dpa iii plus: can, single-wire can, j1939, j1708, j1587, j1922, vpwm j1850, gm uart (aldl), digital i/o, accessories: dg-j1939-04-cable: "y" cable for connecting to dpa ii plus/t (rs232) hardware to the deutsch 6- and 9-pin truck connectors, dg-obdii-o-cable: 6' open-ended cable, dg-j1939-04-cable: "y" cable for connecting to dpa ii plus/t (rs232) hardware to the deutsch 6- and 9-pin truck connectors, dg-j1939-04-cable: "y" cable for connecting to dpa ii plus/t (rs232) hardware to the deutsch 6- and 9-pin truck connectors, dg-obdii-o-cable: 6' open-ended cable, dg-rs-cable: 6' molded female/male rs-232 cable, dg-t

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A30800