

View Online at <https://aerobasegroup.com/nsn/7025-01-504-9811>

**Mounting Type:**

Bracket

**Direct Current Voltage Rating In Volts:**

7.0 and 32.0

**End Application:**

6625-01-445-0085

**Unpackaged Unit Length:**

2.75 inches

**Unpackaged Unit Width:**

5.11 inches

**Unpackaged Unit Height:**

1.25 inches

**Power Source:**

External

**Special Features:**

Hardware features: reverse voltage protection, on-board flash for field upgrades, leds indicating pc and network status, rs-232 driver capable of 230k baud, ce certification (emc), protocols supported: dpa ii plus: can, j1939, j1708, j1587, j1922, dpa iii plus: can, single-wire can, j1939, j1708, j1587, j1922, vpwm j1850, gm uart (aldl), digital i/o, accessories: dg-j1939-04-cable: "y" cable for connecting to dpa ii plus/t (rs232) hardware to the deutsch 6- and 9-pin truck connectors, dg-obdii-o-cable: 6' open-ended cable, dg-j1939-04-cable: "y" cable for connecting to dpa ii plus/t (rs232) hardware to the deutsch 6- and 9-pin truck connectors, dg-j1939-04-cable: "y" cable for connecting to dpa ii plus/t (rs232) hardware to the deutsch 6- and 9-pin truck connectors, dg-obdii-o-cable: 6' open-ended cable, dg-rs-cable: 6' molded female/male rs-232 cable, dg-t

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A30800