

View Online at <https://aerobasegroup.com/nsn/7025-01-508-5742>

Mounting Type:

Plate

Direct Current Voltage Rating In Volts:

5.0

Furnished Items And Quantity:

Bracket connector 1; rack, panel mounting 1; module, brain board 1; harness assembly, interconnect 1; module, analog, input 6; insert, connector, rectangular 1; screw, machine, panhead cross rec 13; screw, machine, panhead cross rec 6; nut, self-locking, hex 26; wire, electric, insulated (60 ft) 1; power supply 1; strap, tiedown, electric component, adjustable 15; wire, electrical xletfe insul (50 ft) 1; strap, ca, self-clinch adjustable 10; module, digital output, i/o snap 1; wire, electric, shielded (30 ft) 1; sleeve, electric insulation, ht shrink (7.5 ft) 1; sleeve, sldr, ht shrink 4; lug, uninsulated, ring tongue 2; contact, electrical, pin 2; mount, tie 4; upper hinge block 9; lower hinge block 9; screw, cap, hex head 9; packing, preformed, o-ring 30; bolt, captive, hex head 30

Current Rating In Amps:

4.0

Power Source:

External

Frequency In Hertz:

47.0 and 64.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A30800