

View Online at <https://aerobasegroup.com/nsn/7025-01-518-1584>

**Alternating Current Voltage Rating In Volts:**

90.0 and 264.0

**Storage Temperature Range:**

-25.0/+70.0 degrees celsius

**Unpackaged Unit Length:**

16.900 inches

**Unpackaged Unit Width:**

10.400 inches

**Unpackaged Unit Height:**

1.700 inches

**Power Source:**

External

**Product Name:**

Brocade silkworm 3200 fabric switch

**Special Features:**

Enclosure back-to-front airflow, power and cable on the same side 1u, 19 inch-eia compliant; operating temperature 10.0 to 40.0 degrees c, humidity type 2 to 85 pct noncondensing at 40 degrees c; nonoperating relative humidity type 90 pct; altitude up to 3,000 m; vibration operating 0.5 gs, 5-500-5hz, nonoperating 2.0 gs, 5-500-5 hz; shock operating 150 gs, 2.7 ms half-sine, nonoperating 60 gs, 13 ms trapezoid; supported power 100 to 240 vac contiguous ; range 90 to 264 vac operational; power consumption 50 watts max

**Frequency In Hertz:**

47.0 and 63.0

**Functional Description:**

Xprovides low-cost switch solution for das to san migration, small san islands, nas back ends, the edge of core-to-edge enterprise sans and hub/loop switch replacement; enables low-cost storage connectivity for server clustering environments; helps increase roi for organizations that need reliable, high-performance sans to support business applications; enables 8-port 1 gbit/sec and 2 gbit/sec intelligent switching at an unprecedented price point; provides full forward and backward compatibility with other brocade silkworm switches; simplifies san deployment and administration through embedded brocade web tools management software; provides the ability to scale from entry 2-switch fabrics to full-feature enterprise-level capabilities

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A30800