

View Online at <https://aerobasegroup.com/nsn/7025-01-518-1584>

Alternating Current Voltage Rating In Volts:

90.0 and 264.0

Storage Temperature Range:

-25.0/+70.0 degrees celsius

Unpackaged Unit Length:

16.900 inches

Unpackaged Unit Width:

10.400 inches

Unpackaged Unit Height:

1.700 inches

Power Source:

External

Product Name:

Brocade silkworm 3200 fabric switch

Special Features:

Enclosure back-to-front airflow, power and cable on the same side 1u, 19 inch-eia compliant; operating temperature 10.0 to 40.0 degrees c, humidity type 2 to 85 pct noncondensing at 40 degrees c; nonoperating relative humidity type 90 pct; altitude up to 3,000 m; vibration operating 0.5 gs, 5-500-5hz, nonoperating 2.0 gs, 5-500-5 hz; shock operating 150 gs, 2.7 ms half-sine, nonoperating 60 gs, 13 ms trapezoid; supported power 100 to 240 vac contiguous ; range 90 to 264 vac operational; power consumption 50 watts max

Frequency In Hertz:

47.0 and 63.0

Functional Description:

Xprovides low-cost switch solution for das to san migration, small san islands, nas back ends, the edge of core-to-edge enterprise sans and hub/loop switch replacement; enables low-cost storage connectivity for server clustering environments; helps increase roi for organizations that need reliable, high-performance sans to support business applications; enables 8-port 1 gbit/sec and 2 gbit/sec intelligent switching at an unprecedented price point; provides full forward and backward compatibility with other brocade silkworm switches; simplifies san deployment and administration through embedded brocade web tools management software; provides the ability to scale from entry 2-switch fabrics to full-feature enterprise-level capabilities

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A30800