Magnetic Tape Transport - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/7025-01-573-1755

Overall Length: 5:000 inches Overall Height: 3:400 inches Overall Width: 9:600 inches EndApplication: Simulator tester an/fpq-25 (v)2, (v)3 Unibesign: Cabinet Voltage In Volts And Current Type: 12:0.0 ac and 240.0 ac Product Name: Drive, tape Suffer Size: 8:0 megabytes Special Features: Transfer rates user native 6mbytes/sec, compressed 12mbytes/sec; drive power specs 65 va 0.53a at 120vac, 0.27a at 240vac, 222 bt/ut/mt Na Life Measure: Na End Measure: Find Measure: Tame Drive, tape Shell Life: Na Drive, tape Shell Life: Na Choir Measure: Drive, tape Shell Life: Na Drive, tape	
Overall Height:3.400 inchesOverall Width:9.600 inches8.600 inchesEnd Application:Simulator tester an/fpq-25 (v)2, (v)3Unit Design:CabinetVotage In Volts And Current Type:120.0 ac and 240.0 acProduct Name:Drive, tapeSuffer Size:8.0 megabytesSpecial Features:Transfer rates user native 6mbytes/sec, compressed 12mbytes/sec; drive power specs 65 va 0.53 at 120vac, 0.27 at 240vac, 222 bt/u/nNaUnit Of Measure:NaDir Of Measure:NaDir Of Measure:NaDir Of Measure:NaDir Of Measure:Tartes User native 6mbytes/sec, compressed 12mbytes/sec; drive power speces 65 va 0.53 at 120vac, 0.27 at 240vac, 222 bt/u/nNaDir Of Measure:NaDir Of Measure:Tartes User Native Sec, Compressed 12mbytes/sec; drive power speces 65 va 0.53 at 120vac, 0.27 at 240vac, 222 bt/u/nNaDir Of Measure:Tartes User Native Sec, Dir Of Measure:Tartes U	Overall Length:
A400 inches Verall Width: 9.600 inches End Application: Simulator tester an/fpq-25 (v)2, (v)3 Unit Design: Cabinet Voltage In Volts And Current Type: Cabinet Voltage In Volts And Current Type: 120.0 ac and 240.0 ac Product Name: Drive, tape Buffer Size: So megabytes Special Features: Transfer rates user native 6mbytes/sec, compressed 12mbytes/sec; drive power specs 65 va 0.53a at 120vac, 0.27a at 240vac, 222 btu/wr Shelf Life: N/a Unit Of Measure:	5.900 inches
Overall Width:9.600 inches9.600 inchesEnd Application:Simulator tester an/fpq-25 (v)2, (v)3Unit Design:Cabinet7 Otage In Volts And Current Type:12.0.0 ac and 240.0 acProduct Name:Drive, tapeBuffer Size:8.0 megabytesSpecial Features:Transfer rates user native 6mbytes/sec, compressed 12mbytes/sec; drive power specs 65 va 0.53a at 120vac, 0.27a at 240vac, 222 bt/urN/aUnit Of Measure:	Overall Height:
9.600 inches End Application: Simulator tester an/fpq-25 (v)2, (v)3 Unit Design: Cabinet Cabinet Voltage In Volts And Current Type: Attack and 240.0 ac Product Name: 120.0 ac and 240.0 ac Product Name: Drive, tape Drive, tape Drive, tape Suffer Size: 8.0 megabytes Suffer Size: 13.0 megabytes Suffer Size: 14.0 megabytes, compressed 12mbytes/sec; drive power specs 65 va 0.53 at 120vac, 0.27 at 240vac, 222 bt//r Sheff Life: N/a N/a Lift Of Measure: -	3.400 inches
End Application: Simulator tester an/fpq-25 (v)2, (v)3 Unit Design: Cabinet Votage In Volts And Current Type: 120.0 ac and 240.0 ac Product Name: Drive, tape 8.0 megabytes Special Features: Transfer rates user native 6mbytes/sec, compressed 12mbytes/sec; drive power specs 65 va 0.53 at 120vac, 0.27 at 240vac, 222 btu/r N/a Lint Of Measure: T.	Overall Width:
Simulator tester an/fpq-25 (v)2, (v)3 Unit Design: Cabinet Cabinet Voltage In Volts And Current Type: 120.0 ac and 240.0 ac Product Name: Drive, tape Buffer Size: 8.0 megabytes Special Features: Transfer rates user native 6mbytes/sec, compressed 12mbytes/sec; drive power specs 65 va 0.53a at 120vac, 0.27a at 240vac, 222 btu/n Shelf Life: N/a Unit Of Measure:	9.600 inches
Unit Design:CabinetVoltage In Volts And Current Type:120.0 ac and 240.0 acProduct Name:Drive, tapeBuffer Size:8.0 megabytesSpecial Features:Transfer rates user native 6mbytes/sec, compressed 12mbytes/sec; drive power specs 65 va 0.53 at 120vac, 0.27a at 240vac, 222 btu/ntShelf Life:N/aLint of Measure:	End Application:
Cabinet Voltage In Volts And Current Type: 120.0 ac and 240.0 ac Product Name: Drive, tape Buffer Size: 8.0 megabytes Special Features: Transfer rates user native 6mbytes/sec, compressed 12mbytes/sec; drive power specs 65 va 0.53a at 120vac, 0.27a at 240vac, 222 btu/nr Shelf Life: N/a Unit Of Measure:	Simulator tester an/fpq-25 (v)2, (v)3
Voltage In Volts And Current Type:120.0 ac and 240.0 acProduct Name:Drive, tapeDrive, tapeBuffer Size:8.0 megabytesSpecial Features:Transfer rates user native 6mbytes/sec, compressed 12mbytes/sec; drive power specs 65 va 0.53 at 120vac, 0.27a at 240vac, 222 btu/hrShelf Life:N/aUnit Of Measure:	Unit Design:
120.0 ac and 240.0 ac Product Name: Drive, tape Buffer Size: 8.0 megabytes Special Features: Transfer rates user native 6mbytes/sec, compressed 12mbytes/sec; drive power specs 65 va 0.53a at 120vac, 0.27a at 240vac, 222 btu/hr Shelf Life: N/a Unit Of Measure: 	Cabinet
Product Name: Drive, tape Buffer Size: 8.0 megabytes Special Features: Transfer rates user native 6mbytes/sec, compressed 12mbytes/sec; drive power specs 65 va 0.53a at 120vac, 0.27a at 240vac, 222 btu/hr Shelf Life: N/a Unit Of Measure:	Voltage In Volts And Current Type:
Drive, tape Buffer Size: 8.0 megabytes Special Features: Transfer rates user native 6mbytes/sec, compressed 12mbytes/sec; drive power specs 65 va 0.53a at 120vac, 0.27a at 240vac, 222 btu/hr Shelf Life: N/a Unit Of Measure:	120.0 ac and 240.0 ac
Buffer Size: 8.0 megabytes Special Features: Transfer rates user native 6mbytes/sec, compressed 12mbytes/sec; drive power specs 65 va 0.53a at 120vac, 0.27a at 240vac, 222 btu/hr Shelf Life: N/a Unit Of Measure: 	Product Name:
8.0 megabytes Special Features: Transfer rates user native 6mbytes/sec, compressed 12mbytes/sec; drive power specs 65 va 0.53a at 120vac, 0.27a at 240vac, 222 btu/hr Shelf Life: N/a Unit Of Measure:	Drive, tape
Special Features: Transfer rates user native 6mbytes/sec, compressed 12mbytes/sec; drive power specs 65 va 0.53a at 120vac, 0.27a at 240vac, 222 btu/hr Shelf Life: N/a Unit Of Measure: 	Buffer Size:
Transfer rates user native 6mbytes/sec, compressed 12mbytes/sec; drive power specs 65 va 0.53a at 120vac, 0.27a at 240vac, 222 btu/hr Shelf Life: N/a Unit Of Measure:	8.0 megabytes
Shelf Life: N/a Unit Of Measure:	Special Features:
N/a Unit Of Measure:	Transfer rates user native 6mbytes/sec, compressed 12mbytes/sec; drive power specs 65 va 0.53a at 120vac, 0.27a at 240vac, 222 btu/hr
Unit Of Measure:	Shelf Life:
	N/a
 Demilitarization:	Unit Of Measure:
Demilitarization:	
	Demilitarization:

Yes - demil/mli

Fiig:

A508g0