

View Online at <https://aerobasegroup.com/nsn/7025-01-655-5556>

**Overall Length:**

22.200 inches

**Overall Height:**

18.950 inches

**Overall Width:**

22.250 inches

**Operating Temperature Range:**

+10.0 to 32.0 degrees celsius

**End Application:**

Vdws (v)6 ti12, an/byg- (v)6 ssn21 cl; vdws(v)2, 3, 4 ti12 ssn688/688i cl; u5040 ti10 byg1 vacls; video distr & wksta byg-1(v)7 ssgn ti10; vid distr&wksta byg-1(v) 2/3 688cl ti10; 005250485, tank assembly

**Paper Feed Mechanism:**

Tray

**Additional Programs:**

5essjfbz6 printer communication language and level 3 postscript

**Resolution Printing Density And Color:**

600.0 dot density horizontal black and white and 1200.0 dot density vertical black and white and 600.0 dot density horizontal color and 1200.0 dot density vertical color

**Print Speed And Color:**

32.0 black and white pages per minute and 26.0 color pages per minute

**Printer Type:**

Laser

**Features Provided:**

Color capable and ruggedized and expandable buffer memory

**Unit Design:**

Desk top

**Criticality Code Justification:**

Agav

**Voltage In Volts And Current Type:**

110.0 ac and 220.0 ac

**Product Name:**

Printer, ritec rlp610; high-speed color laser printer

**Buffer Size:**

256.0 megabytes

**Special Features:**

Designed for shipboard platforms; ruggedized; packaged in shock and vibration isolated, reinforced aluminum frame; table-top mount with isolation; duty cycle: 6000 pages per month average, 60000 pages max; 400 sheet input tray; media: 17 to 32 lb. Bond, letter and legal size

**Type/model Designation:**

Rlp610

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

**Fig:**

A506k0